

# 2016-2019 Chevrolet Malibu

## PART NUMBER: SU-70-03-L

**\*PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM Legend\***

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

**TOOLS REQUIRED:** Dash Trim Removal Tool (DTRT), Cordless Drill, Phillips head screw tip, 9/32 socket and ratchet

**PARTS INCLUDED:** VSM Legend, 2 - #8x1/2 screws

**LOCATION:** Right of Screen

Step 1: Using a DTRT remove bezel that runs from the right passenger vent to just left of the gauge cluster. Start at the passenger side and moving towards the driver's side. Do not disconnect starter button.

Step 2: Remove climate controls but no need to disconnect wires. Remove the 2 9/32 bolts holding radio. These are above where the climate controls were and above hazard button. Behind the radio screen using a DTRT pop out small cover that is cover 2 screws holding the top of the radio. Remove screws. No pull radio screen out as retainer clips are now holding it. No need to disconnect.

Step 3: Position the mount just below the bottom plastic groove (see pic 4). Mark the screw locations. Then drill a pilot hole or screw in provided screws.

Step 4: reverse steps 2 and 1.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1<sup>st</sup> Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

### Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

[View Instructions & Updates Online at www.pro-fit-intl.com](#)