Toyota 4Runner 2010-2016

PART NUMBER: SU-70-03-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drives seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Socket Wrench, 8mm Socket, Cordless Drill

PARTS INCLUDED: VSM Legend, 2-#8 x 3/8

LOCATION: Right of Vent

Step 1: Remove the trim piece on each side of the climate control using a DTRT and your hand to pull it off. (Photo #1)

Step2: Remove the climate control system (held by retainer clips) by grabbing the black part of the temp dial and fan speed dial. Set this aside. There is no need to disconnect the wires.

Step 3: Remove the 4 bolts below the radio that are behind the climate control by using an 8mm socket. (Photo #2) After removing the 4 bolts, pull from top and bottom to remove the radio (top is held by retainer clips).

Step 4: Place the legend mount on the right-hand side of the radio opening (Photo #3). It should sit tight against side and bottom of the slanted groove in plastic. Mark the screw locations or using a cordless drill, screw in the provided screws.

Step 5: Reverse steps 3 to 1.



Pro.Fit International, Inc. * may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. [®] 221 1St Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

View Instructions & Updates Online at www.pro-fit-intl.com