

# Nissan Sentra 2013-2018

## PART NUMBER: TY-71-00-G3

**\*PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3\***

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

**TOOLS REQUIRED:** Dash Trim Removal Tool (DTRT), Cordless Drill, Phillips Screw Driver (Magnet tip is best)

**PARTS INCLUDED:** VSM G3, J-Stem, Lock Plate, 2-#8 x 3/8

**LOCATION:** Right of radio

Step 1: Using the DTRT, remove the trim bezel around the radio. They are held in with retainer clips. This now can be set aside.

Step 2: Remove the 4 screws, 2 on each side of the radio. Then remove the radio and set aside. (No need to disconnect radio). (Photo #1).

Step 3: Place mount on right hand side of the radio opening and mark screw locations or using a cordless drill, screw in the provided screws. (Photo #2)

Step 4: Reverse steps 1 and 2 to complete installation.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1<sup>st</sup> Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

### Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

View Instructions &  
Updates Online at  
[www.pro-fit-intl.com](http://www.pro-fit-intl.com)