



A+

## CASE LED WHITE 3000K

Uplight and downlight luminaire in stylish design for indoor use. Multichip with indirect light creates a fine and decorative light pattern of 140°, excellent as decorative lighting in private and public areas. Integrated driver for connection to 230V. For installation on walls with a concealed connector.

### DESCRIPTION

<b>GTIN:</b>	7392971122151
<b>Item Name:</b>	Case LED White 3000K
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Light Source:</b>	LED
<b>Light Source Included (type):</b>	LED not exchangeable
<b>Instant Full Light:</b>	No
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>85
<b>Colour Consistency (SDCM):</b>	3
<b>Luminaire Lumen (lm):</b>	320
<b>Beam Angle (°):</b>	140
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Indirect
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	L70 50 000h Ta 25°C
<b>Nominal Life Time (h):</b>	50000

### TECHNICAL DATA

<b>Voltage (type):</b>	AC
<b>Voltage Interval (V):</b>	220...240
<b>Voltage Nominal (V):</b>	230
<b>Line Frequency (Hz):</b>	50, 60
<b>Power LED (W):</b>	4
<b>Power Luminaire (W):</b>	6
<b>System Power (W):</b>	6
<b>Energy Efficiency Class:</b>	A+

## OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Screw Terminals
Constant Current (mA):	480
Operating Temperature:	-10...+40
Max. Tc (°C):	85
Dimmable:	No
Type of Dimming:	OnOff

## COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Color Code (RAL):	9016

## MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor / dry locations
IP Degree of Protection:	20
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Protection Class:	I
Width (mm):	100
Height (mm):	70
Depth (mm):	100
Weight (kg):	0,5

