hidealite



CUBE II WHITE 3000K

The simple and clean design makes our popular Cube a classic favourite that illuminates your facade and creates a welcoming appearance. Separate rear element with dual cable bushings and push-in, loop-in, loop-out terminal block for easy installation. IP65 rating and durable surface treatment with sandblasted finish. Integrated driver with adjustable light level via DIP switch. Can be dimmed using external driver. Spacer for surface-mounted cable routing available as an accessory.

DESCRIPTION

GTIN: Item Name: Warranty:

LIGHT TECHNICAL DATA

Light Source: Light Source Included (type): LED Colour: Colour Temperature (K): Colour Rendering Index (Ra): Colour Consistency (SDCM): Luminous Intensity (cd): Luminaire Lumen (Im): Beam Angle (°): Light sharing: Light sharing: Light Outlet: Number of Lamps (pcs): Number of LED (pcs): Life Time: Nominel Life Time (h):

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220240
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power Luminaire (W):	6
System Power (W):	6
Energy Efficiency Class:	A+

7392971129020 Cube II White 3000K 5 years

LED
LED not exchangeable
Warm White
3000
>80
3
2x190
310
50
Symmetric
Direct
2
2
L70 50 000h Ta 25°C
50000



OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Through Wiring:	Yes
Standby Power:	0,7
Constant Current (mA):	300
Operating Temperature:	-20+45
Max. Tc (°C):	65
Dimmable:	No
Type of Dimming:	DIP 30% 60% 100%
Fuse B10 (pcs):	180
Fuse B16 (pcs):	287
Fuse C10 (pcs):	207
Fuse C16 (pcs):	327

COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Color Code (RAL):	9016

MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	65
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK09
Protection Class:	I
Width (mm):	100
Height (mm):	100
Depth (mm):	100
Weight (kg):	1

























