



A+

GLOBE G2 SURFACE WHITE TUNE

Exclusive surface-mounted downlight in modern design with cupped reflector. Deeply placed light source gives a glare-free light. The appearance of the luminaire can be reinforced with reflectors in various colours to match choices of materials and interior. Globe G2 is the natural choice for homes as well as hotels and restaurants. For surface mounting directly in ceiling or directly across coupling, ceiling or appliance box. Including integrated mains dimmable driver. Dimmable with the most commonly available dimmers on the market.

DESCRIPTION

| | |
|-------------------|-----------------------------|
| GTIN: | 7392971136172 |
| Item Name: | Globe G2 Surface White Tune |
| Warranty: | 5 years |

LIGHT TECHNICAL DATA

| | |
|--------------------------------------|----------------------|
| Light Source: | LED |
| Light Source Included (type): | LED not exchangeable |
| LED Colour: | Tune |
| Colour Temperature (K): | 2700 |
| Range Colour Temperature (K): | Tune 2000-2700 |
| Colour Rendering Index (Ra): | >95 |
| Colour Consistency (SDCM): | 3 |
| Luminous Intensity (cd): | 850 |
| Luminaire Lumen (lm): | 440 |
| Beam Angle (°): | 36 |
| Light sharing: | Symmetric |
| Light Outlet: | Direct |
| Number of Lamps (pcs): | 1 |
| Number of LED (pcs): | 1 |
| Life Time: | L70 80 000h Ta 25°C |
| Nominal Life Time (h): | 80000 |
| Life Time Driver: | 50 000h/3% |

TECHNICAL DATA

| | |
|------------------------------|-----------|
| Adjustable: | No |
| Voltage (type): | AC |
| Voltage Interval (V): | 220...240 |
| Voltage Nominal (V): | 230 |
| Line Frequency (Hz): | 50 |
| Power LED (W): | 6,5 |
| Power Luminaire (W): | 7,5 |
| System Power (W): | 7,5 |
| Efficiency Luminaire (lm/W): | 59 |
| Efficiency System (lm/W): | 59 |
| Energy Efficiency Class: | A+ |



OPERATION AND CONNECTION

| | |
|--------------------------------|--|
| Driver Included: | Yes |
| Driver Model: | Constant Current |
| Driver Type: | Built-in |
| Connection (type): | Quick Terminal |
| Connection (mm2): | 3x0,75-1,5 |
| Through Wiring: | Yes |
| Strain Relief: | Yes |
| Operating Temperature: | -20...+40 |
| Max. Tc (°C): | 85 |
| Dimmable: | Yes |
| Type of Dimming: | Trailing Edge, Leading Edge |
| Memory Function Power Failure: | No |
| Protection Against: | Short Circuit, Overheating 110°C, Overload |
| Fuse B10 (pcs): | 60 |
| Fuse B16 (pcs): | 90 |
| Fuse C10 (pcs): | 73 |
| Fuse C16 (pcs): | 110 |

COLOR AND MATERIAL

| | |
|-------------------|-----------|
| Material: | Aluminium |
| Color: | White |
| Color Code (RAL): | 9016 |

MEASUREMENT AND INSTALLATION

| | |
|--------------------------------|------------------------|
| Operation Environment: | Indoor / dry locations |
| IP Degree of Protection: | 20 |
| Installation: | Surface mounted |
| Mounting Installation: | Screw Mounting |
| Approval Marks: | CE, SELV |
| Filament Test IEC 695-2-1(°C): | 650 |
| Protection Class: | I |
| Height (mm): | 68 |
| Diameter (mm): | 115 |
| Weight (kg): | 0,76 |



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

hidealite Globe G2 Surface 874/2012

A++
A+
A
B
C
D
E

LED

