



A

MILO XL DOWN ANTHRACITE 4000K

Ceiling light in timeless design for installation flat against the ceiling. Good glare free reflector technology with high lumen output. IP55 rating, anodised and powder coated for tough environments. Simple installation thanks to separate rear element with dual cable bushings and push-in terminal block for through wiring. Spacers and cover ring for surface mounted cable included, facilitates installation on uneven ceilings and simplifies row installation. Built-in mains dimmable driver.

DESCRIPTION

GTIN:	7392971138091
Item Name:	Milo XL Down Anthracite 4000K
Warranty:	5 years

LIGHT TECHNICAL DATA

Light Source:	LED
Light Source Included (type):	LED not exchangeable
LED Colour:	White
Colour Temperature (K):	4000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	2000
Luminaire Lumen (lm):	1300
Beam Angle (°):	36
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L70 60 000h Ta 25°C
Nominal Life Time (h):	60000
Life Time Driver:	50 000h/10%

TECHNICAL DATA

Weighted Energy Consumption (kWh/1000h):	16
Adjustable:	No
Voltage (type):	AC
Voltage Interval (V):	220...240
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	13
Power Luminaire (W):	16
System Power (W):	16
Efficiency Luminaire (lm/W):	81
Efficiency System (lm/W):	81
Energy Efficiency Class:	A

OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,75-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Operating Temperature:	-20...+40
Max. Tc (°C):	80
Dimmable:	Yes
Type of Dimming:	Trailing Edge
Memory Function Power Failure:	No

COLOR AND MATERIAL

Material:	Aluminium
Color:	Antracit
Color Code (RAL):	7016
Halogen free:	No

MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	55
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK06
Protection Class:	I
Height (mm):	139
Diameter (mm):	100
Weight (kg):	0,74



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

hidealite Milo XL Down 874/2012

A++
A+
A
B
C
D
E
F

LED

