



A+

## MILO XXL II GREY 3000K

Wall luminaire in a timeless design with both up- and downward light for lighting large properties and facades. Impact resistant (IK09) cylinder-shaped luminaire that creates security and provides good lighting during the dark hours of the day. Easily installed thanks to separate rear element and push-in, loop-in, loop-out terminal block for direct connection to 230V. IP65 model, anodised with durable powder coating for tough environments. Comes with integrated driver and spacers for surface-mounted cable routing.

### DESCRIPTION

<b>GTIN:</b>	7392971137995
<b>Item Name:</b>	Milo XXL II Grey 3000K
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Light Source:</b>	LED
<b>Light Source Included (type):</b>	LED not exchangeable
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	2x3700
<b>Luminaire Lumen (lm):</b>	3400
<b>Beam Angle (°):</b>	36
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	2
<b>Number of LED (pcs):</b>	2
<b>Life Time:</b>	L70 100 000h Ta 25°C
<b>Nominal Life Time (h):</b>	100000
<b>Lumen maintenance 50 000h:</b>	L88
<b>Lumen maintenance 100 000h:</b>	L70
<b>LLMF @ 50 000h:</b>	0,88
<b>LLMF @ 100 000h:</b>	0,7
<b>Life Time Driver:</b>	50 000h/10%

## TECHNICAL DATA

Adjustable:	No
Voltage (type):	AC
Voltage Interval (V):	220...240
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	30,6
Power Luminaire (W):	34
System Power (W):	34
Efficiency Luminaire (lm/W):	98
Efficiency System (lm/W):	98
Energy Efficiency Class:	A+

## OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,75-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Factor $\lambda$ :	0,9
Efficiency (%):	91
Operating Temperature:	-20...+40
Max. Tc (°C):	95
Dimmable:	No
Type of Dimming:	OnOff
Fuse B10 (pcs):	6
Fuse B16 (pcs):	9
Fuse C10 (pcs):	20
Fuse C16 (pcs):	32

## COLOR AND MATERIAL

Material:	Aluminium
Mercury Free:	Yes
Color:	Grey
Color Code (RAL):	7042
Halogen free:	No

## MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	65
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK09
Filament Test IEC 695-2-1(°C):	650
Protection Class:	I
Width (mm):	140
Height (mm):	296
Depth (mm):	180
Diameter (mm):	140
Weight (kg):	2,35



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

hidealite Milo XXL II 874/2012

A++  
A+  
A  
B  
C  
D  
E

LED

