



A+

MILO XXL I GREY 3000K

Wall luminaire in timeless design with downward light source for lighting large properties and facades. Impact resistant (IK09) cylinder-shaped luminaire that creates security and provides good lighting during the dark hours of the day. Easily installed thanks to separate rear element and push-in, loop-in, loop-out terminal block for direct connection to 230V. IP65 model, anodised with durable powder coating for tough environments. Comes with integrated driver and spacers for surface-mounted cable routing.

DESCRIPTION

GTIN:	7392971137971
Item Name:	Milo XXL I Grey 3000K
Warranty:	5 years

LIGHT TECHNICAL DATA

Light Source:	LED
Light Source Included (type):	LED not exchangeable
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	3800
Luminaire Lumen (lm):	1800
Beam Angle (°):	36
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L70 100 000h Ta 25°C
Nominal Life Time (h):	100000
Lumen maintenance 50 000h:	L88
Lumen maintenance 100 000h:	L70
LLMF @ 50 000h:	0,88
LLMF @ 100 000h:	0,7
Life Time Driver:	50 000h/10%

TECHNICAL DATA

Adjustable:	No
Voltage (type):	AC
Voltage Interval (V):	220...240
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	17
Power Luminaire (W):	19,5
System Power (W):	19,5
Efficiency Luminaire (lm/W):	94
Efficiency System (lm/W):	94
Energy Efficiency Class:	A+

OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,75-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Factor λ :	0,9
Efficiency (%):	90
Operating Temperature:	-20...+40
Max. Tc (°C):	85
Dimmable:	No
Type of Dimming:	OnOff
Fuse B10 (pcs):	4
Fuse B16 (pcs):	6
Fuse C10 (pcs):	7
Fuse C16 (pcs):	12

COLOR AND MATERIAL

Material:	Aluminium
Mercury Free:	Yes
Color:	Grey
Color Code (RAL):	7042
Halogen free:	No

MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	65
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK09
Filament Test IEC 695-2-1(°C):	650
Protection Class:	I
Width (mm):	140
Height (mm):	218
Depth (mm):	180
Diameter (mm):	140
Weight (kg):	1,75



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

hidealite Milo XXL I 874/2012

A++
A+
A
B
C
D
E

LED

