



## SLOT IN MINI 82

### CODE CONFIGURATOR

3000K CRI>90	2700K CRI>90
LED 1x4W 420lm 350mA	LED 1x4W 395lm 350mA
24° · 36°	
IP20 · IP44	
L82 x W40 x H30mm	
✂ Cut-out: L78 x W32 x H35mm	
LED DRIVER NOT INCLUDED, SEE DRIVERLIST	



## SLOT IN 180

### CODE CONFIGURATOR

3000K CRI>90	2700K CRI>90
LED 1x8W 840lm 350mA	LED 1x8W 790lm 350mA
24° · 36°	
IP20 · IP44	
L180 x W40 x H30mm	
✂ Cut-out: L165 x W32 x H35mm	
LED DRIVER NOT INCLUDED, SEE DRIVERLIST	



## SLOT IN 430

### CODE CONFIGURATOR

3000K CRI>90	2700K CRI>90
LED 2x8W 1680lm 350mA	LED 2x8W 1580lm 350mA
24° · 36°	
IP20 · IP44	
L430 x W40 x H30mm	
✂ Cut-out: L415 x W32 x H35mm	
LED DRIVER NOT INCLUDED, SEE DRIVERLIST	



## SLOT IN 1500

### CODE CONFIGURATOR

3000K CRI>90	2700K CRI>90
LED 4x8W 3360lm 350mA	LED 4x8W 3170lm 350mA
24° · 36°	
IP20 · IP44	
L1500 x W40 x H30mm	
✂ Cut-out: L1485 x W32 x H35mm	
LED DRIVER NOT INCLUDED, SEE DRIVERLIST	



## SLOT IN 2000

### CODE CONFIGURATOR

3000K CRI>90	2700K CRI>90
LED 6x8W 5040lm 350mA	LED 6x8W 4750lm 350mA
24° · 36°	
IP20 · IP44	
L2000 x W40 x H30mm	
✂ Cut-out: L1985 x W32 x H35mm	
LED DRIVER NOT INCLUDED, SEE DRIVERLIST	



## SLOT IN 3000

### CODE CONFIGURATOR

3000K CRI>90	2700K CRI>90
LED 8x8W 6720lm 350mA	LED 8x8W 6330lm 350mA
24° · 36°	
IP20 · IP44	
L3000 x W40 x H30mm	
✂ Cut-out: L2985 x W32 x H35mm	
LED DRIVER NOT INCLUDED, SEE DRIVERLIST	



# DRIVERLIST FOR SLOT IN

Number of fixtures allowed per driver

		MAINS DIMMABLE:							
Product nr		WL DRIVER01		WL DRIVER02		WL DRIVER03		WL DRIVER09	
Dimensions (LxWxH) mm		102x38x21		113x44x28		99x39x23		38x27x21	
FIXTURE	mA	min	max	min	max	min	max	min	max
SLOT IN 82	350	2	2	3	4	1	2	1	1
SLOT IN 180	350	1	1	2	2	1	1	-	-
SLOT IN 430	350	-	-	1	1	-	-	-	-

Product nr		WL DRIVER02-02		WL DRIVER02-03		WL DRIVER02-04			
Dimensions (LxWxH) mm		113x44x28 (2pcs)		113x44x28 (3pcs)		113x44x28 (4pcs)			
FIXTURE	mA	min	max	min	max	min	max		
SLOT IN 1500	350	1	1	-	-	-	-		
SLOT IN 2000	350	-	-	1	1	-	-		
SLOT IN 3000	350	-	-	-	-	1	1		

		1-10V DIMMABLE:							
Product nr		WL DRIVER05		WL DRIVER06					
Dimensions (LxWxH) mm		110x52x23,5		237x30x21					
FIXTURE	mA	min	max	min	max				
SLOT IN 82	350	1	3	1	4				
SLOT IN 180	350	1	1	1	2				
SLOT IN 430	350	-	-	1	1				

Product nr		WL DRIVER06-02		WL DRIVER06-03		WL DRIVER06-04			
Dimensions (LxWxH) mm		237x30x21 (2pcs)		237x30x21 (3pcs)		237x30x21 (4pcs)			
FIXTURE	mA	min	max	min	max	min	max		
SLOT IN 1500	350	1	1	-	-	-	-		
SLOT IN 2000	350	-	-	1	1	-	-		
SLOT IN 3000	350	-	-	-	-	1	1		

		DALI DIMMABLE:							
Product nr		WL DRIVER07*		WL DRIVER08*					
Dimensions (LxWxH) mm		157x42x32		157x42x32					
FIXTURE	mA	min	max	min	max				
SLOT IN 82	350	1	3	1	4				
SLOT IN 180	350	1	1	1	2				
SLOT IN 430	350	-	-	1	1				

Product nr		WL DRIVER08-02*		WL DRIVER08-03*		WL DRIVER08-04*			
Dimensions (LxWxH) mm		157x42x32 (2pcs)		157x42x32 (3pcs)		157x42x32 (4pcs)			
FIXTURE	mA	min	max	min	max	min	max		
SLOT IN 1500	350	1	1	-	-	-	-		
SLOT IN 2000	350	-	-	1	1	-	-		
SLOT IN 3000	350	-	-	-	-	1	1		

(\*) DRIVER DOES NOT FIT THROUGH CUTOUT HOLE OF FIXTURE  
 (!! WHEN MULTIPLE SPOTS ON 1 DRIVER: CONNECT SERIAL