



AL Series Chains

Dimensions: inch

PEER Chain No.	Lacing	Pitch	Pin Diam.	Pin Length Over-all	Plate Thickness	Plate Height	Average Tensile Strength Lbs.	Average Weight Per Foot Lbs.
		P	D	F	T	H (max.)		
AL-322	2 x 2	0.375	0.141	0.266	0.050	0.300	2,310	0.13
AL-422	2 x 2	0.500	0.156	0.318	0.060	0.410	3,960	0.25
AL-444	4 x 4	0.500	0.156	0.572	0.060	0.410	7,920	0.48
AL-466	6 x 6	0.500	0.156	0.826	0.060	0.410	11,880	0.73
AL-522	2 x 2	0.625	0.200	0.414	0.080	0.513	6,600	0.41
AL-544	4 x 4	0.625	0.200	0.748	0.080	0.513	13,200	0.80
AL-566	6 x 6	0.625	0.200	1.082	0.080	0.513	19,800	1.20
AL-622	2 x 2	0.750	0.234	0.490	0.094	0.615	9,240	0.51
AL-644	4 x 4	0.750	0.234	0.880	0.094	0.615	18,480	1.01
AL-666	6 x 6	0.750	0.234	1.270	0.094	0.615	27,320	1.50
AL-688	8 x 8	0.750	0.234	1.660	0.094	0.615	36,960	2.02
AL-822	2 x 2	1.000	0.312	0.654	0.125	0.820	15,840	1.00
AL-844	4 x 4	1.000	0.312	1.182	0.125	0.820	31,680	1.88
AL-866	6 x 6	1.000	0.312	1.710	0.125	0.820	47,520	2.79
AL-888	8 x 8	1.000	0.312	2.238	0.125	0.820	63,360	3.70
AL-1022	2 x 2	1.250	0.375	0.802	0.156	1.025	25,300	1.68
AL-1044	4 x 4	1.250	0.375	1.454	0.156	1.025	50,600	2.59
AL-1066	6 x 6	1.250	0.375	2.106	0.156	1.025	74,800	4.97
AL-1088	8 x 8	1.250	0.375	2.758	0.156	1.025	101,200	5.88
AL-1222	2 x 2	1.500	0.437	0.938	0.187	1.230	37,560	2.30
AL-1244	4 x 4	1.500	0.437	1.718	0.187	1.230	65,120	4.62
AL-1266	6 x 6	1.500	0.437	2.498	0.187	1.230	97,680	5.83
AL-1288	8 x 8	1.500	0.437	3.278	0.187	1.230	130,240	8.10

When ordering chain with odd number of pitches specify whether male or female end link required.