

# TWO-PIECE SAFETY CLAMPING COLLARS

PART NUMBER		PRODUCT SPECIFICATIONS			
BLACK OXIDE STEEL	STAINLESS STEEL	BORE SIZE	OD	WIDTH	CLAMP SCREW
GH2C-012-B	GH2C-012-SS	1/8	13/16	1/4	4-40
GH2C-018-B	GH2C-018-SS	3/16	13/16	1/4	4-40
GH2C-025-B	GH2C-025-SS	1/4	13/16	1/4	4-40
GH2C-031-B	GH2C-031-SS	5/16	13/16	1/4	4-40
GH2C-037-B	GH2C-037-SS	3/8	1 1/16	5/16	6-32
GH2C-043-B	GH2C-043-SS	7/16	1 1/16	5/16	6-32
GH2C-050-B	GH2C-050-SS	1/2	1 1/4	3/8	8-32
GH2C-056-B	GH2C-056-SS	9/16	1 1/4	3/8	8-32
GH2C-062-B	GH2C-062-SS	5/8	1 1/2	13/32	10-32
GH2C-068-B	GH2C-068-SS	11/16	1 1/2	13/32	10-32
GH2C-075-B	GH2C-075-SS	3/4	1 3/4	1/2	1/4-28
GH2C-081-B	GH2C-081-SS	13/16	1 3/4	1/2	1/4-28
GH2C-087-B	GH2C-087-SS	7/8	1 7/8	1/2	1/4-28
GH2C-093-B	GH2C-093-SS	15/16	1 7/8	1/2	1/4-28
GH2C-100-B	GH2C-100-SS	1	2	1/2	1/4-28
GH2C-106-B	GH2C-106-SS	1 1/16	2	1/2	1/4-28
GH2C-112-B	GH2C-112-SS	1 1/8	2 1/8	1/2	1/4-28
GH2C-118-B	GH2C-118-SS	1 3/16	2 1/8	1/2	1/4-28
GH2C-125-B	GH2C-125-SS	1 1/4	2 1/4	1/2	1/4-28
GH2C-131-B	GH2C-131-SS	1 5/16	2 1/4	1/2	1/4-28
GH2C-137-B	GH2C-137-SS	1 3/8	2 3/8	1/2	1/4-28
GH2C-143-B	GH2C-143-SS	1 7/16	2 3/8	1/2	1/4-28
GH2C-150-B	GH2C-150-SS	1 1/2	2 1/2	1/2	1/4-28
GH2C-156-B	GH2C-156-SS	1 9/16	2 1/2	1/2	1/4-28
GH2C-162-B	GH2C-162-SS	1 5/8	3	5/8	5/16-24
GH2C-168-B	GH2C-168-SS	1 11/16	3	5/8	5/16-24
GH2C-175-B	GH2C-175-SS	1 3/4	3	5/8	5/16-24
GH2C-187-B	GH2C-187-SS	1 7/8	3 1/4	5/8	5/16-24
GH2C-193-B	GH2C-193-SS	1 15/16	3 1/4	5/8	5/16-24
GH2C-200-B	GH2C-200-SS	2	3 1/4	5/8	5/16-24
GH2C-212-B	GH2C-212-SS	2 1/8	3 1/2	5/8	5/16-24
GH2C-218-B	GH2C-218-SS	2 3/16	3 1/2	5/8	5/16-24
GH2C-225-B	GH2C-225-SS	2 1/4	3 1/2	5/8	5/16-24
GH2C-237-B	GH2C-237-SS	2 3/8	3 1/2	5/8	5/16-24
GH2C-243-B	GH2C-243-SS	2 7/16	4	3/4	3/8-24
GH2C-250-B	GH2C-250-SS	2 1/2	4	3/4	3/8-24
GH2C-262-B	GH2C-262-SS	2 5/8	4 1/4	3/4	3/8-24
GH2C-268-B	GH2C-268-SS	2 11/16	4 1/4	3/4	3/8-24
GH2C-275-B	GH2C-275-SS	2 3/4	4 1/4	3/4	3/8-24
GH2C-287-B	GH2C-287-SS	2 7/8	4 1/2	3/4	3/8-24
GH2C-293-B	GH2C-293-SS	2 15/16	4 1/2	3/4	3/8-24
GH2C-300-B	GH2C-300-SS	3	4 1/2	3/4	3/8-24



## GH2C-SERIES

Clamping design fully engages the shaft without marring or other shaft damage

Effective on hard and soft shafts

Recessed screw head provides an outside surface free of major projections

Two-piece collars may be easily installed where major disassembly would otherwise be required

Other sizes and materials available

