



### British Standard Chains

Dimensions: inch

PEER Chain No.	Pitch P	Roller		Plate			Pin Diam. D	Overall Width		Transverse Pitch K	Average Ultimate Strength Lbs.	Average Weight Per Foot Lbs.
		Width	Diam.	Height	Thickness			F	G			
		W	R	H	T1	T2						
04B	0.236	0.110	0.157	0.196	0.023	0.023	0.072	0.129	0.161	-	720	0.08
05B	0.315	0.118	0.196	0.265	0.031	0.031	0.090	0.153	0.181	-	1,140	0.11
08B	0.500	0.192	0.305	0.450	0.049	0.049	0.161	0.244	0.279	-	3,300	0.30
06B-1	0.375	0.225	0.250	0.325	0.049	0.049	0.129	0.255	0.283	-	2,300	0.30
06B-2	0.375	0.225	0.250	0.325	0.039	0.049	0.129	0.449	0.488	0.403	4,300	0.52
06B-3	0.375	0.225	0.250	0.325	0.049	0.049	0.129	0.657	0.697	0.806	6,610	0.85
08B-1	0.500	0.305	0.335	0.462	0.059	0.059	0.175	0.318	0.358	-	4,070	0.45
08B-2	0.500	0.305	0.335	0.462	0.059	0.059	0.175	0.598	0.661	0.548	8,150	0.90
08B-3	0.500	0.305	0.335	0.462	0.059	0.059	0.175	0.886	0.949	1.096	12,120	1.35
10B-1	0.625	0.379	0.400	0.578	0.064	0.064	0.200	0.381	0.417	-	5,620	0.65
10B-2	0.625	0.379	0.400	0.578	0.064	0.064	0.200	0.713	0.772	0.653	11,240	1.30
10B-3	0.625	0.379	0.400	0.578	0.064	0.064	0.200	1.043	1.102	1.306	16,750	1.90
12B-1	0.750	0.459	0.475	0.635	0.070	0.070	0.225	0.437	0.480	-	7,380	0.87
12B-2	0.750	0.459	0.475	0.635	0.070	0.070	0.225	0.823	0.874	0.766	14,760	1.75
12B-3	0.750	0.459	0.475	0.635	0.070	0.070	0.225	1.224	1.260	1.532	22,040	2.60
16B-1	1.000	0.670	0.625	0.814	0.124	0.156	0.325	0.692	0.775	-	16,310	1.81
16B-2	1.000	0.670	0.625	0.814	0.124	0.156	0.325	1.319	1.409	1.255	32,620	3.60
16B-3	1.000	0.670	0.625	0.814	0.124	0.156	0.325	1.960	2.050	2.510	49,600	5.30
20B-1	1.250	0.770	0.750	1.026	0.124	0.173	0.401	0.780	0.961	-	20,060	2.45
20B-2	1.250	0.770	0.750	1.026	0.124	0.173	0.401	1.520	1.654	1.435	40,100	4.90
20B-3	1.250	0.770	0.750	1.026	0.124	0.173	0.401	2.217	2.400	2.870	60,170	7.30

PEER Chain No.	Pitch P	Roller		Plate			Pin Diam. D	Overall Width		Transverse Pitch K	Average Ultimate Strength Lbs.	Average Weight Per Foot Lbs.
		Width	Diam.	Height	Thickness			F	G			
		W	R	H	T1	T2						
24B-1	1.500	1.000	1.000	1.315	0.189	0.219	0.575	1.059	1.256	-	33,060	4.70
24B-2	1.500	1.000	1.000	1.315	0.189	0.219	0.575	1.988	2.218	1.903	66,120	9.20
24B-3	1.500	1.000	1.000	1.315	0.189	0.219	0.575	2.952	3.162	3.806	99,180	13.70

Note: Chain available in Nickel Plated and Stainless Steel.  
T1 = PIN LINK (OUTSIDE) PLATE  
T2 = ROLLER LINK (INSIDE) PLATE