


# SLV-Series, Sleeve Valve



SLV-Series sleeve valves combines high flow capability with short stroke in a small package. Unlike ball valves, sleeve valves do not require space for a handle.

SLV-Series sleeve valves features smooth opening/closing operation. Outlet is exhausted to atmosphere when the valves is closed. Unit is constructed of brass body and anodized aluminum sleeve for corrosion resistance.

Symbol



## HOW TO ORDER

**SLV** — □ □  
 Sleeve Valve      Connection (NPT)  
                             18 = 1/8", 28 = 1/4"  
                             38 = 3/8", 48 = 1/2"

## SPECIFICATIONS

ITEM	MODEL	SLV-18	SLV-28	SLV-38	SLV-48
CONNECTION	NPT	1/8" M-F	1/4" M-F	3/8" M-F	1/2" M-F
FLUID		AIR			
VALVE FUNCTION		2-POSITION, 3-WAY, VENT TO EXHAUST			
LENGTH	IN. (mm)	2-11/16" (68.0)	2-27/32" (72.0)	3" (76.0)	3-5/8" (92.0)
HEX	IN. (mm)	5/8" (16.0)	43/63" (17.0)	3/4" (19.0)	61/64" (24.0)
SLEEVE DIAMETER	IN. (mm)	1-3/16" (30.0)	1-3/16" (30.0)	1-3/16" (30.0)	1-7/8" (47.5)
MATERIAL	BODY	BRASS			
	SLEEVE	ANODIZED ALUMINUM			
OPERATING PRESSURE		0 ~ 140 PSI (0 ~ 10 kg/cm <sup>2</sup> )			
OPERATING TEMPERATURE		41° ~ 140°F (5° ~ 60°C)			
WEIGHT	OZ.	3.30	3.38	3.69	9.06