


# Stainless Steel Bearing Inserts



## SSB Set Screw Lock, Narrow Inner Race Relubricatable

Balls & Rings 440 Stainless Steel  
 Seal Silicone Rubber  
 Slinger & Seal Frame 302 Stainless Steel  
 Retainer 302 Stainless Steel  
 Set Screws 410 Stainless Steel  
 Lubrication H-1 Food Grade Grease



CORROSION RESISTANT

Bearing No.	Bore Dia. of Bearing		Dimensions (in. (mm))							Basic Load Rating (lbs.)	Basic Static Load Rating (lbs.)	Weight (lbs.)
	<i>d</i>	<i>d</i>	<i>Be</i>	<i>D</i>	<i>Bi</i>	<i>N</i>	<i>M</i>	<i>G</i>	<i>Ds</i>			
SSB 201-8	1/2	0.4724	1.5748	0.8661	0.2362	0.6299	0.1575	10-32UNF	1,770	830	0.22	
202-10	5/8	12.0	40.0	22.0	6.0	16.0	4.0					
SSB 204-12	3/4	0.5512	1.8504	0.9843	0.2756	0.7087	0.1969	1/4-28UNF	2,440	1,220	0.33	
204	20	14.0	47.0	25.0	7.0	18.0	5.0					
SSB 205-14	7/8	0.5906	2.0472	1.0630	0.2953	0.7677	0.2165	1/4-28UNF	2,670	1,440	0.40	
205	25	15.0	52.0	27.0	7.5	19.5	5.5					
SSB 206-18	1 1/8	0.6299	2.4409	1.1417	0.3150	0.8267	0.2362	1/4-28UNF	3,710	2,020	0.60	
206	30	16.0	62.0	29.0	8.0	21.0	6.0					
206-19	1 9/16											
206-20	1 1/4 S											
SSB 207-20	1 1/4	0.6693	2.8346	1.2598	0.3346	0.9252	0.2362	5/16-24UNF	4,930	2,780	0.93	
207-22	1 3/8	17.0	72.0	32.0	8.5	23.5	6.0					
207	35											
207-23	1 7/16											