



**MODELO: 3363 VENTILADOR DE PARED 76,2 cm
30" WALL FAN**

PILRAM S.A. DE C.V.

Av. López Mateos #1Lote 4, San Lorenzo Rio Tenco, Cuautitlán Izcalli, C.P 54713
Tel. 55-5872-9082 www.pilram.com

DESEMPEÑO PERFORMANCE	Velocidad de flujo de Aire (a 1 m de distancia)	Air Flow Velocity (1 m)	3= 4.6 m/s 2= m/s 1= m/s
	RPM		3=1085 2= 970 1= 860
	Oscilacion	Oscillation	95 °
	Inclinacion	Tilt	
ELECTRICO ELECTRIC	Amp (Velocidad Alta) A	Amperage (High Speed)	1.71 A
	Potencia (Velocidad Alta) W	Watts (High Speed)	206 W
CARACTERISTICAS FEATURES	Dimension del Producto ensamblado	Unit Dimension	Altura: 80 cm Base: 33 cm
	Controles: Electronico/Digital, Boton de Presion (mecanico) or Interruptor Giratorio (Mecanico)	Controls: Electronic/Digital, Mechanical Push Button or Mechanical Rotary Switch	Interruptor giratorio
	Control Remoto (alambrico , inalambrico)	Remote Control (Basic, Full- Featured, etc.)	No
	Numero de velocidades	Number of speeds	3
	Fusible protector termico	Thermic Fuse	SI
	Para montar en pared	Wall Mount	Si
	Cable (tipo y especificaciones)	Cord (type & rating)	SJT 600V, 9' 18AWGX3C
	Longitud del cable	Cord Length	8'
	Aspa: # de hojas y material	blade	3 hojas (metalicas)
	Otras características:	Other features:	
CERTIFICACION	Certiificacion NOM-003-SCFI-200	NOM approved	NOM-424-ANCE
	UL certificacion	UL approved	No
EMBARQUES SHIPPING	Dimension de empaque del producto	Carton Dimension	975 mm x 170 mm x 850 mm
	Volumen	ft ³	4.98 ft ³
	Peso Neto (Kg/lbs)	Net Weight (Kg/lbs)	15.2 kg
	Peso Bruto (Kg/lbs)	Gross Weight (Kg/lbs)	17.4 kg
	Cantidad aprox. contendor	HC Quantity (aprox)	48' 610 pcs 53' 678 pcs
	Garantia	Warranty	Un Año 1 Year
	Codigo de barras	Barcode	EAN 13: 7501409033635 UPCA : 681944033639

PILRAM S.A. DE C.V.

 Av. López Mateos #1Lote 4, San Lorenzo Rio Tenco, Cuautitlán Izcalli, C.P 54713
 Tel. 55-5872-9082 www.pilram.com