

Teno

Heated & Non-Heated Towel Rails

VARIATIONS

Heated Version	Non-Heated Version	Height x Width	Volts	Watts/rail
TFH1-83	TNH1-83	900 x 830 mm	24V	66 Watts




NOTES

- This is a Low Voltage product
- Transformer required - TRTR220-24V (Sold separately)
- Concealed wiring available through either foot.
- Wire specifications: Use flexible multistrand 1.5mm² - Do not exceed 5 meters in length.
- Non Heated version available (Less 10%)
- Plug-In version not available

STANDARD FINISHES

Mirror Polished Stainless Steel RRP	Brushed Stainless Steel +20% (Stocked)	Matt Black/White Painted +40% (Stocked)	Gunmetal PVD +50% (Stocked)	Brushed Gold PVD +60% (Stocked)
--	---	--	--	--

SPECIFICATIONS

Voltage 24 Volts	Standards AS/NZ 60335.2.43	DEVELOPED IN AUSTRALIA 
Material Stainless Steel 304	Electrical Connection Concealed Wiring only - any leg (Transformer required)	HEATING TIME 30 MINUTES 
Finish Mirror Polished	Heating Method Dry Internal Heating Element	WARRANTY 10 YEAR 
Ingress Protection IPX5 (Suitable for wet areas)	Non-Heated version available	

