



Monster Linear Light

HLL111.5 Series



ELECTRICAL:

Input Voltage: See _LDM 700 spec
 Input Current: See _LDM 700 spec

WARNING !!!

**Use Only Spectrum Illumination LDM Driver with Monster Lights.
 Do Not Connect Monster Lights Directly to 24VDC!**

ENVIRONMENTAL:

Operating Temperature: 0 to 50°C
 Relative Humidity: 5 to 85% non-condensing

MECHANICAL:

Connector: M12 Quick Connect, 5 pin Reverse Key
 Weight: 4.3 lbs. (1.95Kg)

ILLUMINATION:

Light Source: LED – 6 Colors, UV & IR
 Quantity HB LED's: 12
 Light Emitting Pattern: 11.5" / 292mm
 LED Life: up to 100,000 hours*.
 *Contact us for LED life information



PART NUMBER DESIGNATION: HLL111.5-XXX

XXX = Light Color – See "Dash #" in table below:

Color	Dash #	λ Dominant Typical	λ Dominant Range	Spectral Half-width $\Delta\lambda$ %	λ Peak Typical	Units
Infrared	-940	935	n/a	45	940	nm
Infrared	-850	845	n/a	40	850	nm
Red	-630	625	620 - 650	20	638	nm
Amber	-590	590	584 - 598	14	592	nm
Green	-530	530	519 - 561	35	522	nm
Cyan	-505	505	489 - 521	30	503	nm
Blue	-470	470	459 - 491	25	464	nm
Ultra Violet	-395	395	390 - 410	n/a	n/a	nm
Ultra Violet	-365	365	n/a	8	365	nm
White	-WHI	Color Temp 5700 - 7000K				




Light includes LDM DIN rail mount constant current driver, 4-meter cable (driver is available with variable or 0-10VDC intensity control - cable also available in 8, 15 and 30-meter lengths).

Monster Lights have changeable lenses for matching the area of illumination with the working distance



Monster Lenses - P/N HLL111.5-XXX/XX
12° Narrow (Standard) /16 – 16° Frosted Narrow
/30 – 30° Medium Angle /23 – 23° Frosted Medium
/50 – 50° Medium Angle /39 – 39° Frosted Wide
/F – ~70° Wide Angle /R60 – 60° Reflectors
/L – 44° x 12° Angle /R – 90° Reflectors



*** UV lights are standard with 60° reflectors, other options available. ***