

General Purpose Thinner

Production Description

General Purpose Thinner is formulated specially for spray applications. General Purpose Thinner is based on various solvent in order to achieve optimal performance, featuring fast drying and great compatibility with different systems such as alkyd, acrylic, lacquer, polyurethane and epoxy. It can also be used as cleaning solvent for equipment and tools.

Areas of Application

Recommended to be used as thinner or clean-up solvent for 2 pack epoxy and 2 pack polyurethane. Can also be used as thinner for other solvent based products.

Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.80
Boiling Range	80-120 °C
Thinning Recommendations	Addition of 10-15% may be used, depending on product type and application equipment.
Packs available	1 litre, 4 litre, 20 litre, 60 litre & 200 litre

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone NSW 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed Nov 2018