

HT 600 SERIES

HT 613 - HT 618 - HT 621

The water softeners in the HT 600 series are high performance systems, specially designed for applications where space is limited.

In addition to the clever, space-saving design, the softeners are packed with features making them an ideal choice, even when space is not at a premium.

- Soft water 24/7
- Metered water use, so the system will only regenerate when necessary
- Cabinet with wheels for easy movement



World Leading
Founded in 1970, Kinetico is considered a world leader in water treatment solutions.



Non-Electric
Powered by the kinetic energy of moving water.



Twin Tank Design
Guarantees a continuous and uninterrupted supply of soft water.



Metered Regeneration
Use is measured to ensure it only regenerates when necessary.



Soft Water Rinse
Uses soft, conditioned water to self-clean, prolonging the life of the unit.






Countercurrent Regeneration
Regenerates from the bottom up.



Low Salt Consumption
Economical to use, highly efficient system.

HT 600 SERIES

	HT 613		HT 618		HT 621	
						
						
	Dimensions, mm		Dimensions, mm		Dimensions, mm	
Min. Flow (L/m)	20		22		25	
Max. Flow@1bar (L/m)	25		28		30	
Disc Selection:	dH	L	dH	L	dH	L
1	4	2280	5	2280	7	2280
2	8	1140	10	1140	14	1140
3	11	760	15	760	21	760
4	15	570	20	570	28	570
5	19	456	25	456	35	456
6	23	380	30	380	42	380
7	26	325	35	325	48	325
8	30	285	40	285	56	285
Regeneration:						
Salt consumption (kg)	0,5 kg		0,75 kg		1,0 kg	
Time (minutes)	11		11		11	
Volume (litres)	34		34		34	
Media volume (litres)	2 x 4,5		2 x 7		2 x 9	
Salt capacity (kg)	20		27		36	
Inlet/outlet connections	3/4"		3/4"		3/4"	
Max pressure (bar)	7,0 Bar		7,0 Bar		7,0 Bar	
Min pressure (bar)	2,5 Bar		2,5 Bar		2,5 Bar	
Max temperature °C	2 - 65		2 - 65		2 - 65	