



We care about the Environment

By refraining from inserting a full printed manual with our Argon Audio products we save more than 20 tons of paper each year.

See back side of this insert for Quick start guide

Safety Instructions



- Unplug this product from the wall outlet before cleaning. Do not use this product near water or moisture. Do not spill liquids on the product. Clean only with a dry cloth.
- Place the unit on a solid surface.
- Do not put it in a closed bookcase or a cabinet that may keep air from flowing through its ventilation openings.
- Do not install near any heat sources, such as radiators, heat registers, stoves or other appliances that produce heat.
- Protect the power cord from being walked on or pinched, particularly at plugs and the point where they exit from the product.
- During Lightning storms, unplug the product from the power source or if unused for long periods of time. This will prevent lightning and power-line surge damage to the product.

- Do not attempt to service this product yourself. Opening or removing covers may expose you to dangerous voltages or other hazards. Please contact the manufacturer to be referred to an authorized service center near you.
- Do not overload wall outlets, extension cords, or integral power circuits as this can result in a risk of fire or electric shock.
- Never push any object through the product openings, as this can result in fire, electric shock or damage.
- Use proper power sources. Plug the product into a proper power source, as described in the operating instructions or as marked on the product.



If there is a Lightning flash with an arrow head on the product, it's intended to alert the User of the presence of un-insulated "dangerous voltage" within the product, that might be of sufficient magnitude to constitute a risk of electric shock to persons.



If there is an Exclamation point on the product, it's intended to alert the User that there is important operating and maintenance (servicing) information in the User manual.



TT Quick start

Quick start - Set-up

- Install the Lid carefully over the hinge prongs.
- Install the drive belt over the inner ring under the platter and make sure it won't fall off during the setup. Place the platter

through the turntable spindle, then rotate the platter until you see the drive motor pulley through the window at the top left corner. Carefully grab the drive belt and put it around the slot of motor pulley.



- Connect the power adapter to the turntable and power on the turntable.
- Set the Motor Start/Stop switch to the Start position to see if the platter motor spins. If the platter does not spin, try the steps listed above again.
- 5. Place the slipmat on the platter.
- 6. For cartridge down force adjustment use the counterweight supplied in the box. Gently push and turn the counterweight onto the arm tube stub. Lower the arm lift and position the cartridge in the space between arm rest and platter. Carefully rotate the counterweight until the arm tube balances out. The arm should return to the balanced position if it is moved up or down. This adjustment must be done carefully. Do not forget to remove the cartridge protection cap if fitted.

- Once the tonearm is correctly balanced return it to its rest.
 Hold the counterweight without moving it, and gently rotate the down force scale ring until the zero is in line with black line on the rear of the tonearm. Check whether the arm still balances out.
- Rotate the counterweight counter clockwise (seen from the front) to adjust the down force. One mark on the scale represents 0.05g of down force. The recommended down force for the factory fitted cartridge is 3.0±0.5g.
- For connecting the TT to an amplifier: This turntable uses a
 moving magnetic cartridge and has a RIAA amplifier built in. If
 you are using a separate phono input or phono amplifier, set the
 RIAA ON/OFF Switch on the back to OFF mode. For
 connection all other inputs (AUX, Video, CD etc.) set the
 RIAA Switch to ON.

Notice: You can find a full User Manual in PDF format for this product on www.argonaudio.com