



Demand more. Choose Foster

BCT15-7 Blast Chiller Cabinet

BCT15-7



Temperature



Blast Chiller 70/3 °C

Dimensions (mm)

W 755 D 690

H 890



Capacity

15 Chilling (Kg)

7 Freezing (Kg)

Packed Weight

95 KG

Features & Benefits

The Foster tray loading blast chiller range provides the ideal way to ensure quality and food safety is maximised in every kitchen, large or small

- Dedicated 15Kg blast chiller with occasional 7Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior & interior – the 'gold standard' in performance finishes
- Intuitive touch control panel – just press and go!
- A range of intelligent chilling & freezing programmes to ensure foods are chilled safely and that quality is maintained

| External Finish | |
|--------------------------------------|----------|
| 304 Stainless Steel | Standard |
| Internal Finish | |
| 304 Stainless Steel | Standard |
| Shelving | |
| Additional Shelf | Option |
| Nylon Coated Gastronorm 1/1 Shelf | Option |
| Stainless Steel Gastronorm 1/1 Shelf | Option |
| Bakery Tray - 60x40 | Option |
| Base Fittings | |
| 80mm Castors | Standard |
| Legs | Option |
| Levelling Bolts | Option |

| Doors | |
|---------------------|----------|
| Solid Full | Standard |
| Hinged - Right Hand | Standard |
| Hinged - Left Hand | Option |

| Worktop & Drawers | |
|-------------------|--|
| □ | |

| Refrigeration | |
|-------------------------------|----------|
| Integral | Standard |
| Remote - less condensing unit | Option |
| R404a | Standard |
| Drain Required? | No |

| Electrical Data & Service Information | |
|---------------------------------------|----------|
| 230 Volts | Standard |
| 50Hz | Standard |
| 60Hz | Option |
| 1 Phase | Standard |
| Thermal Heat Rejection (W) | 1,217 |
| Noise (dBa @ 1m) | 67.3 |
| Fuse Required (A) | 13 amp |

| Product Extras | |
|------------------------------------|----------|
| Door Pull Handle | Standard |
| Hold Facility | Standard |
| Temperature Probe | Standard |
| Hardwired Logging System Interface | Option |

Footnotes

- Chilling Capacity: 15KG. Freezing capacity: 7KG 70oC to 3oC in less than 90 minutes within specifications, entry temperature up to 90oC for chilling.
- *Please add 55mm to depth for spacer

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster