# F900 SERIES

## **G9084 Four Burner Gas Counter Top**





#### **Short Form Specification**

Unit to be Falcon F900 Series four burner gas counter top having 4 x 9.5kW gas burners. Unit to be supplied upon adjustable feet and or upon an open stand. Unit will have four individual cast iron pan supports.

High performance burners with removable cap for ease of cleaning to have flame failure device as standard to stop gas supply to in the event of the burners being extinguished in error. Each burner is to be lit by means of a pilot which will have a protection hood – to prevent clogging. The burners will be held within a deep drawn pressed well to contain spillages and allowing easy cleaning.

The hob will be constructed from 2mm 304 grade stainless steel. Hobs will be laser cut with right-angled edges to allow joining of units with no gaps between hobs. Exterior panels are Scotch Brite finish stainless steel. Control knobs to be marked showing gas positions and to have a bezel behind each knob to prevent water ingress.

Unit will be for use with natural, propane or butane gas and be supplied with conversion kit.

#### **Key Features**

- 4 x high performance 9.5kW burners
- Individually protected burner pilots
- Burners fitted with flame failure device as standard
- Individual cast iron pan supports
- Pressed, sealed burner well to contain spillage
- Supplied upon adjustable stainless steel feet
- 2mm thick 304 grade stainless steel hob
- Laser cut hob allows edge to edge joining of units
- Stainless steel external panels with Scotch Brite finish
- For use with natural, propane and butane gas. Conversion kit supplied with each unit
- Dynamic link system compatible



Integrated linking system allows quick and easy installation to create a continuous cookline. *UK Patent No. 2540131* 

### Accessories

- Front hob rail
- Fixed or mobile stand

### **G9084 Four Burner Gas Counter Top**



#### Model Dimensions (mm) 800 800 900 175 gas inlet -1-=1 350 Φ Φ Φ Ф Φ Ф Ф Ф $\square$ 575 gas inlet 40 gas inlet The unit can be connected at the rear or from below. 40 gas inlet 40 gas inlet <u> Timerae l'asrae</u> 725 gas inlet 006 575

Unit on castors is the same hob height.

### **Specification Details**

	Natural Gas	Propane Gas	Butane Gas
Total rating (kW - Nett)	38	28	28
Total rating (btu/hr - gross)	142,662	105,119	105,119
Inlet size	3/4" BSP	3/4" BSP	3/4" BSP
Flow rate	3.73m <sup>3</sup> /hr	2.04kg/h	2.00kg/h
Inlet pressure <i>(mbar)</i>	20	37	29
Operating pressure (mbar)	20	37	29
Hob burner rating (kW - Nett)	9.5 x 4	7 x 4	7 x 4
Hob burner rating (btu/hr - gross)	35,666 x 4	26,280 x 4	26,280 x 4
Weight <i>(kg)</i>	68	68	68
Packed weight (kg)	84	84	84
Packed dimensions (mm)	1000 (w) x 1000 (d) x 780 (h)		

gas inlet