



KOREA DIGITAL WEIGHING INDICATOR

FEATURES

- A compact appearance by DIN regulations.
- Easy to set up, check several values by the numeral key
- Improved a convenience and precision of operating by message function.
- Can make several key function use or disuse.
- Watch-dog timer guards for self-diagnostics
- Available to change the function of the external input terminal.
- Back up of weight even electric spark case.
- Function available to change the unit value.
- RS-232 interface



SPECIFICATIONS

Art No.	E-2101C
Item No.	01ES-D-WI007
Display	Multiple LED Color Display
Max Display	1000000
Keypad	Key (0-9), CLR, SET, PRINT
Dimension (L x W x H)	198 x 99 x 136mm
Zero Adjust Range	-4mV ~ 42.0mV
Load Cell Supply Voltage	DC 10V (±5V)
Max. Load Cell Input Voltage	32mV
A/D Conversion	130,000 count
Character Size (Height)	20mm
Temperature	-10°C ~ 40°C
Temperature Coefficient	± 20ppm / °C
Non-Linearity Range	0.005% Full Of Scale
A Digit	x1, x2, x5, x10, x20, x50
Moisture	85% RH Max
Indicator Weight	Net 2.3kg, Packing 3.3kg
Power Voltage	AC 110 / 220V (±10%), 50/60 Hz