

ELECTRONIC WEIGHING INDICATOR

FEATURES

- Function keys: With Tare x 2, Units, Net/Gross, Print, Zero, On, Off
- Straight Weighing Function, Counting Function, Check Weighing HI - OK - LO Function, Multiple Weighing Units Available, Hold (Animal) Function.
- Power On Zero Tracking, Auto Calibration, Auto Power off Mode, Digital Noise Filter, Full Tare, Accumulation Memory, Programmable Capacity And Division, Low Battery Indicator And Charging Status Indicator.



OPTIONS

• RS232 Output / Relay Output

SPECIFICATIONS

Art No.	ESWI-CWB
Item No.	01ES-D-WI014
Display	Extra-Large 40mm High, 6 Digits LCD With White Backlight
Resolution	2 x 3000e
Dimensions	245W x 110D x 185H (mm)
Sensitivity	0.12uV/d Minimum
Analog Input	0.6 mV/V ~ 3mV/V
Speed	30 Times Per Second
Weighing Units	Kilogram And Pound
Load Cell	Up to 4 x 350 ohm Minimum Resistance
Operating Environment	-10°C to 40°C (14°F to 104°F)
Power Source	Rechargeable Battery 6V/4Ah Or
Tomo: Godine	Input DC 100V ~ 240V Switching Power
Quantity Offer	5 pcs & 10 pcs