

Microlab Prep

Your New Lab Partner



How Do You Prep?

Laboratory automation can revolutionize the work in any lab, bringing speed and consistency to pipetting work that is often monotonous and prone to error. Trading the hand pipettes for automation is often a huge investment for a lab, taking money to get started and automation engineering to properly set up workflows. The affordable and user-friendly solution is the Hamilton[®] Microlab[®] Prep.™

P TEP

The Prep is automation that easily fits onto a lab bench, is built for ease of use and speed, and all at a price that's affordable for any lab. Plus, it's backed by Hamilton's quality engineering, with the same precise liquid handling and robust hardware that you can find in even the largest automation solutions. Whether you are getting started with lab automation or just need automation to relieve the hand pipetting in your lab, the Microlab Prep is your answer.



Started

Define Workflow

HAMILTON COMPANY:
HELPING INNOVATE THE
JOURNEY OF DISCOVERY

Classic Hamilton Quality, Tiny Footprint

Hamilton has earned a reputation for top-quality automation with solutions that support science in labs around the world again and again. The Microlab Prep takes Hamilton's workhorse automation and boils it down into a 3 square foot footprint. With the reliable automation features Hamilton is known for, plus a few new innovations, the Microlab Prep is ready to revolutionize the repetitive work in your lab.

Capacitive Liquid Level Detection (cLLD) and Clot Detection

The Microlab Prep channels are equipped with capacitance and pressure sensors that enable capacitive liquid level detection (cLLD) and clot detection. Hamilton's black conductive tips facilitate capacitance sensing, enabling channels to detect the liquid level in labware. Sensitive pressure sensors enable pressure monitoring during the aspiration process, notifying users of aspiration difficulties such as clots or empty wells.

Air Displacement Pipetting

The Microlab Prep uses air displacement technology, which is similar technology to using a hand pipette, without the issues associated with liquid-filled automated pipetting systems. Air displacement allows for high pipetting accuracy and precision with a dynamic pipetting range of 1–1000 μ L. Take advantage of the precision, with less maintenance and reduced risk of contamination or sample dilution.



Superior Liquid Handling Technology: CO-RE® II

Automated liquid handling applications require precise tip attachment and positioning. To ensure this precision, all Hamilton liquid handling workstations, including the Microlab Prep, offer proprietary Compressed O-Ring Expansion (CO-RE II) technology. CO-RE II technology attaches disposable tips or CO-RE II Paddles to the pipetting channels with a robust lock-and-key style mechanism. The system requires no vertical force for tip attachment or tip ejection, eliminating mechanical stress and improving overall system reliability, pipetting speed, positional accuracy, and dexterity.



Built-in Labware Detection for Speed


Every Microlab Prep features a camera mounted to the top of the workstation that detects and identifies the labware placed on the deck. Camera-identified labware makes programming new protocols easy to breeze through, without reading through long lists of choices. It also enables proper verification of labware on the deck when running a protocol that has already been programmed, double checking that the deck is filled with the right labware in the right places.

Simple Touchscreen Programming

Say hello to minimal and modern software that's as easy to use as your smartphone. Build and simulate new protocols using thoughtfully designed wizards for common pipetting actions. With a library of protocols at the ready, tap and run any protocol. It's as low fuss as using a hand pipette, except you'll never have to worry about carpal tunnel.


Build the Prep for Your Lab


At Hamilton, we don't believe that one size fits all. Even with the small footprint of the Microlab Prep, you can choose what tools and features you need to get the most out of automation for your lab.





Prep systems









Barcode Scanner

Fume Hood Integration Kit





CO-RE® Paddles

Hamilton Heater Shaker

Pipetting Options

75 – 125 mm H

The Microlab Prep features three possible configurations for pipetting automation.

30 - 50 mm H

2 Channels

This configuration features two Hamilton CO-RE II channels. Channels can move independently and are compatible with a wide range of Hamilton CO-RE II tips. This standard configuration provides the most flexibility for pipetting to different labware types, including reagent reservoirs, tubes, and plates.

8 Multi-Probe Head

This configuration features a set of eight Hamilton CO-RE II channels that operate together and are compatible with a wide range of Hamilton CO-RE II tips. This standard configuration is optimized for pipetting speed across ANSI/SLAS standard 96-well plates.

2 Channels + 8 Multi-Probe Head

This configuration features two independently operable Hamilton CO-RE II channels in addition to the eight channels that operate together. This upgraded configuration offers the most versatility overall, with independent channels for labware flexibility and the 8 MPH for stamping speed.


Quickly Compare


| | 2 Channels | 8 Multi-Probe Head | 2 Channels + 8 Multi-Probe Head |
|---|---------------------------------------|--|---|
| Number of pipetting actions that can take place at one time | 2 | 8 | 2 or 8 |
| Compatible with ANSI/SLAS 96-well plates | Yes | Yes | Yes |
| Compatible with ANSI/SLAS 384-well plates | Yes | Yes | Yes |
| Compatible with reagent reservoirs | Yes | Yes | Yes |
| Compatible with tubes | Yes | No | Yes |
| Additional Information | Flexibly works with all labware types | Optimized to complete pipetting tasks quickly and in bulk for compatible labware types | Features both configurations to ensure flexibility and expedience for all pipetting tasks |


7

Programming with a Few Easy Taps


Most automation software is designed for a clunky desktop computer with interfaces so complicated that it seems like you need a software engineer to get the most from it. Not with the Microlab Prep. With a mounted touchscreen interface, you can design a new protocol with a few taps of your finger. The software interface was designed to be as easy to use as your smartphone, with step-by-step wizards for set up, runtime, and maintenance. Stepping away from the hand pipette was never as easy as it is now.







The Microlab Prep's one of a kind camera ensures that labware is loaded correctly prior to a run, alerting users if labware is missing or incorrect labware was loaded.











The run screen shows you exactly what is happening during your run when critical samples are on deck. You can see how much time is left, which action is being performed, and what steps are remaining.




The Mircolab Prep has several features that can support a laboratories compliance with the United States Food and Drug Administration's 21 CFR Part 11.10 regulation, including generation of records and limited system access.





Hamilton provides programmed maintenance and service routines to ensure that your Prep is functioning properly.



Pick Your Pipetting Tips

Hamilton provides a wide range of CO-RE II tips that support a diversity of volumes and automation activity. CO-RE II tips are designed to fit together with the O-Rings in each Hamilton pipetting channel, meaning better precision for your liquid handling and less wear and tear on your hardware in the long run.



| Available Options | P/N | Case |
|--|--------|--|
| 50 μL Conductive Non-Sterile Filter Tip | 235948 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 50 μL Conductive Non-Sterile Non-Filter Tips | 235966 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 50 μL Conductive Sterile Filter Tips | 235979 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 50 μL Conductive Sterile Non-Filter Tips | 235978 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 50 μL Nested Conductive Non-Sterile Non-Filter Tips | 235947 | Case of 11,520 tips (NTR 5 x 4 stack) |
| 50 μL Nested Conductive Sterile Non-Filter Tips | 235987 | Case of 11,520 tips (NTR 5 x 4 stack) |
| 300 μL Conductive Non-Sterile Filter Tips | 235903 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 300 μL Conductive Non-Sterile Non-Filter Tips | 235902 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 300 μL Conductive Sterile Filter Tips | 235938 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 300 μL Conductive Sterile Non-Filter Tips | 235937 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 300 μL Nested Conductive Non-Sterile Non-Filter Tips | 235950 | Case of 11,520 tips (NTR 5 x 4 stack) |
| 300 μL Nested Conductive Sterile Non-Filter Tips | 235985 | Case of 11,520 tips (NTR 5 x 4 stack) |
| 1000 μL Conductive Non-Sterile Filter Tips | 235905 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 1000 μL Conductive Non-Sterile Non-Filter Tips | 235904 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 1000 μL Conductive Sterile Filter Tips | 235940 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| 1000 μL Conductive Sterile Non-Filter Tips | 235939 | Case of 5760 tips (Blister 5 x 96 tips per rack) |
| *Ole and in the state of the st | | |

^{*}Clear tip also available for purchase.


Microlab Prep Accessories and Consumables

| Available Options | P/N | Case |
|--|---------------|--|
| 24 Position Small Tube Rack | 6600409-01 | 24 position tube rack (Compatible tube size: 9.5–11.5 mm OD, 30–50mm H) |
| Framed Tip Rack | 6600553-01 | Rack for framed tips |
| 24 Position Large Tube Rack | 6600555-01 | 24 position tube rack (Compatible tube size: 10.5–16 mm OD, 75–125 mm H)) |
| Reagent Reservoir Rack | 6600700-01 | 5 x 60 mL reagent rack |
| Handheld Barcode Scanner | 6603432-01 | 1D handheld barcode scanner |
| Fume Hood Kit | 6603189-01 | Stand and cables for touch screen and enclosure removal |
| 2 mm Hamilton Heater Shaker | 6601885-02 | Heats up to 105 °C and Shakes up to 2500 rpm |
| 3 mm Hamilton Heater Shaker | 6601885-01 | Heats up to 105 °C and Shakes up to 2500 rpm |
| Invitrogen 96 Position Post Magnetic Plate | 94696-01 | Compatible magnetic plate for bead based extractions |
| Applied Biosys, Ambion, 96 Ring Stand Magnet | OTP-TMOI-0051 | Compatible magnetic plate for bead based extractions |
| Alpaqua Magnum FLX Magnetic Plate | OTP-ALPQ-0008 | Compatible magnetic plate for bead based extractions |
| Alpaqua Magnum EX Magnetic Plate | OTP-ALPQ-0007 | Compatible magnetic plate for bead based extractions |
| Alpaqua 96S Ring Magnetic Plate | OTP-A001322 | Compatible magnetic plate for bead based extractions |
| 2 Channel CO-RE II O-Ring Kit | 6607080-01 | 2 pack replacement CO-RE II O-Rings |
| 10 Channel CO-RE II O-Ring Kit | 6607080-02 | 10 pack replacement CO-RE II O-Rings |
| Silicone Oil | 6603044-01 | Lubrication for yearly maintenance |
| Verification Kit with two Framed Tip Racks | 6604125-01 | Photometric and gravemetric volume verification kit; includes two framed tip racks |
| Verification Kit (Liquids and Labware) | 6604125-02 | Photometric and gravemetric volume verification kit |
| Biohazard Waste Bags | 6603183-01 | Tip waste bags (50 per roll) |

Specifications



24 in (609.6 mm)



24 in (609.6 mm)



Size and Weight

| Size W x H x D | 21 in (533.4 mm) x 24 in (609.6 mm) x 24 in (609.6 mm) (32 in height with door open) |
|----------------|--|
| Weight | 85 lbs (38.6 kg) |

Operation

| Deck Capacity | 8 Positions |
|-----------------------|--------------------------------|
| Communication | Ethernet, USB |
| Operating Temperature | 15 °C to 35 °C |
| Operating Humidity | 15% to 85% R.H. non-condensing |

Storage

| Storage Temperature | -20 °C to 70 °C |
|---------------------|--------------------------------|
| Storage Humidity | 10% to 90% R.H. non-condensing |

Power Supply and Procurement Requirements

| Input Specs | Power supply must accept input between 100 VAC to 240 VAC +/- 10% at 50 to 60 hz |
|--------------|--|
| Output Specs | 500 W @ 48 VDC |

Work Accessibility

8 ANSI/SLAS microplate footprint deck positions

Pipetting Specifications for Microlab Prep Channels

| Nominal Tip Size | Pipetted Volume | Trueness | Precision |
|------------------|-----------------|----------|-----------|
| 50 μL | 1 μL | 5.00% | 5.00% |
| 50 μL | 5 μL | 2.50% | 2.00% |
| 50 μL | 50 μL | 2.00% | 1.00% |
| 300 μL | 30 μL | 2.00% | 1.50% |
| 300 μL | 300 μL | 1.00% | 1.00% |
| 1000 μL | 100 μL | 2.00% | 1.00% |
| 1000 μL | 1000 μL | 1.00% | 1.00% |



Hamilton Company specializes in the development, manufacturing, and customization of precision measurement devices, automated liquid handling workstations, and sample management systems.

Hamilton's processes are optimized for quality and flexibility. Whether it's a custom needle with a quick delivery time frame, a special length pH sensor, or a comprehensive solution to fully automate your assay workflow, trust that Hamilton's products will always meet your needs.

Our Complete Portfolio



Laboratory Products

Hamilton Laboratory Products manufactures Microliter™ and Gastight® syringes that set the standard for analytical fluid measurement. Other products include custom needles, semi-automated diluters and dispensers, polymeric HPLC columns, pH electrodes, pipettes, and more.



Robotics

Hamilton Robotics provides automated liquid handling workstations and laboratory automation technology for the scientific community. With a focus on innovative design, our products incorporate Hamilton's patented liquid handling technologies for fully automated solutions. In addition to liquid handling platforms, we also offer application-specific solutions, small devices, and consumables.



Storage

Hamilton Storage offers ultra-low temperature automated sample management systems for storage of a variety of labware. Hamilton's line of biobanking and compound management systems, benchtop devices, and consumables are designed for sample integrity, flexibility, and reliability.



Process Analytics

Hamilton Process Analytics includes innovative solutions for the on-line measurement of pH, dissolved oxygen, conductivity, ORP, viable cell density, and total cell density. Hamilton's proprietary Arc^{\circledcirc} intelligent sensor technology eliminates the need for transmitters and moves the functionality to your smartphone or tablet.



OEM Solutions

Many of the world's top manufacturers utilize Hamilton products and expertise to get their innovations to market faster with lower development and manufacturing costs. As an OEM partner, we offer the ability to integrate our proven syringe pumps or pipetting channels, customize our proven liquid handling platforms, or design a complete system to automate your novel chemistry.

Hamilton Company has been a leading global manufacturer for more than 60 years, with headquarters in Reno, Nevada; Franklin, Massachusetts; Timişoara, Romania; and Bonaduz, Switzerland; and subsidiary offices throughout the world.

Supporting You in the Lab

Hamilton is here for you to make sure your Microlab Prep keeps running in great condition after it's set up in your lab. Hamilton has been in business stocking labs with quality equipment since 1953, and we're here to support you and your workstation for the long haul.



Easy, Independent Maintenance

No service contracts are needed to maintain the Microlab Prep. The Prep was designed to be easy to care for without the need for outside assistance.



Getting Help from Hamilton

Hamilton has a dedicated Microlab Prep Product Support team to answer software and hardware related questions. Visit us at www.hamiltoncompany.com/prephelp to browse help articles or to ask a Microlab Prep related question by submitting a support ticket.



Ordering Replacement Parts

To perform maintenance and replace parts on the Prep, contact us by visiting hamiltoncompany.com/prephelp. Hamilton support wants to make sure you get the right parts for your device and will help guide your selection before you make a purchase.



Keeping Stocked with Consumables

Tips and other consumables are a regular part of liquid handling, and Hamilton has the supplies you need. Visit us at www.hamiltoncompany.com/consumables to browse the online catalog.



HAMILT@N°

To find a subsidiary or distributor in your area, please visit, www.hamiltoncompany.com/contacts.

Web: www.hamiltoncompany.com/robotics Email: marketingrequest@hamiltoncompany.com

United States +1-775-858-3000

United Kingdom, Ireland +44 (0) 121 272 92 80

Brazil +55 (11) 126 50562 **China** +86 21 6164 6567

Denmark, Norway, Sweden, Finland +46 (0) 8 410 273 73

France +33 184 008 420

Germany, Switzerland, Austria, Benelux +49 (089) 248 804 808

Italy +39 39 689 33 93

Japan +81 3 6435 6850

Spain, Portugal +34 930 186 262