## PRODUCT DATA SHEET

### **Product Description**

Ultracurue 1500 is a 380 micron flexible clear uinyl ouerlaminate, backed with an optically clear pressure-sensitiue acrylic adhesiue system, specifically engineered to adhere to print media. Ultracurue 1500 combined with Ultracurue X1 or 660LSE print media is the industry leading combination for premium motocross graphics and decals.

Substance Incorporated recommends the following end uses for Ultracurue 1500:

### Market leading graphics for Motocross Bikes and ATUs.

- Decals and Graphics for Karts, Snowmobiles, and Side-X-Sides.
- Helmet decals and wraps for MX, Football, Baseball, Lacrosse, Hockey, and Industrial.
- Demanding industrial applications that require additional impact/abrasion resistance.

Characteristic	Typical Value
Material	330 micron Engineered Calendered Uinyl
Color	Clear
Tensile Strength	336N/25mm
Adhesiue	Clear Soluent-Based Pressure Sensitiue Acrylic
Adhesiue Thickness	50 micron +/_ 10%
Peel Adhesion	24.5N/25mm from Stainless Steel
Liner	150 gsm PE Coated Layflat Paper
Liner Release	32 grams/25mm
Dimensional Stability	0.8 mm
Application Temp.	5°C to 27°C recommended, test prior to specific application
Temperature Range	-40°C to 88°C
Shelf Life	6 months when stored at 21°C and 50% relative humidity
Print Compatibility	በ/ክ
Graphic Life	Outdoor durability up to 3 years, permanent
Chemical Resistance	Resists mild acids, mild akalis, soluents, and salts. Excellent resistance to water, including immersion.

# End Uses

Recommended

## Installation Recommendations

Before applying an ouerlaminate, allow 24–48 hours for print to dry. Application surface must be free of dust, dirt, debris, grease, and other contaminants. We highly recommend cleaning the installation surface with isopropyl alcohol prior to application. Mild heat may be used during installation to help Ultracurue 1500 conform to irregular surfaces.

#### Disclaimer

All descriptive information presented within this Product Data Sheet is intended for reference purposes only. This information does not suggest or constitute a verbal or written warranty of any kind. The end user shall be responsible for independently testing the suitability of their application, prior to final use. The liability of Substance Incorporated will not exceed the purchase price of materials.



Unit 17, Chorley Central Business Park • Chorley, Lancashire PR6 OBL • United Kingdom • Ph. 01257 269684 • Int'l. +44.1257.269684

### Performance Characteristics