Safety Data Sheet

Issue Date: 29-Jun-2015 Revision Date: 31-May-2016 Version 1

1. IDENTIFICATION

Product Identifier

Product Name Water and Stain Repellant

Other means of identification

SDS # ASP-019

Product Code Angelus 851-05-000

UN/ID No UN1950

Recommended use of the chemical and restrictions on use
Recommended Use Water and stain repellant.

Details of the supplier of the safety data sheet

Supplier Address

Angelus Shoe Polish Co.

Florence Ave.

Santa Fe Springs, CA 90670

Ph: 562-941-4242

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Aerosol spray Physical state Aerosol

Classification

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases Under Pressure	Compressed Gas

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard statements

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do not induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hexane	110-54-3	60-90
Hydrocarbon Propellant	68476-86-8	5-30

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a poison center or

doctor/physician.

Skin Contact Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a poison center or doctor/physician. If breathing has stopped, give artificial

respiration.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs spontaneously, keep

> head below hips to prevent aspirating vomitus into lungs. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Immediately call a

poison center or doctor/physician.

Most important symptoms and effects

Symptoms May be harmful in contact with skin. Causes skin irritation. Dermatitis may occur. Can

> cause defatting of skin tissue. May cause drowsiness or dizziness. High vapor/aerosol concentrations are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system

effects, including death.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or

even death due to chemical pneumonia.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Foam. Water spray (fog).

Unsuitable Extinguishing Media Avoid spraying water directly into storage containers due to a danger of boil over.

Specific Hazards Arising from the Chemical

Contains gas under pressure; may explode if heated. Product is an extremely flammable aerosol. This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

Hazardous Combustion Products Carbon oxides.

Explosion Data

Sensitivity to Static Discharge Prevent electrostatic charge build-up by using common bonding and ground techniques.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating, flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See

Section 12, Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Persons not wearing protective equipment should leave area until cleanup is completed.

Eliminate all ignition sources. Ventilate area of leak or spill. Soak up and contain spill with

an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up absorbed

material and shovel into suitable containers for disposal. For waste disposal, see section 13

of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Use personal protective equipment as required. Wash face, hands,

and any exposed skin thoroughly after handling. Do not breathe

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Do not

expose to temperatures exceeding 50 °C/122°F. Protect from sunlight.

Empty containers retain product residue and can be hazardous. **Packaging Materials**

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm	TWA: 50 ppm TWA: 180 mg/m ³
		(vacated) TWA: 180 mg/m ³	

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Make

emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure. The use of mechanical dilution ventilation is recommended whenever this product is used in

a confined space, is heated above ambient temperatures, or is agitated.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Face shield and chemical anti-splash safety goggles. Refer to 29 CFR 1910.133 for eye

and face protection regulations.

Skin and Body Protection Impervious gloves should be worn. Gloves contaminated with the product should be

discarded. Polyfluorinated polyethylene gloves have been suggested. Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse. Refer to 29 CFR 1910.138 for appropriate skin and body

protection.

Respiratory Protection If TLV is exceeded, use a NIOSH/MSHA approved respirator for organic vapors, Refer to

29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash contaminated

clothing before reuse.

Not determined

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol
Appearance Aerosol spray
Color Not determined

rosol spray Odor Not determined t determined Odor Threshold Not determined

<u>Property</u> <u>Values</u>

pH Not determined
Melting Point/Freezing Point Not determined
Boiling Point/Boiling Range Not determined

Flash Point -93.3 °C / -136 °F Evaporation Rate Post Not determined

Evaporation Rate Flammability (Solid, Gas)

Flammability Limits in Air

Upper Flammability Limits Not determined **Lower Flammability Limit** Not determined **Vapor Pressure** Not determined Vapor Density Not determined **Relative Density** Not determined Water Solubility Completely soluble Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

Remarks • Method

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

ASP-019 - Water and Stain Repellant Revision Date: 31-May-2016

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Do not expose to temperatures exceeding 50 °C/122°F.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Eye contact may result in tearing, redness & pain.

Skin Contact May be harmful in contact with skin. Causes skin irritation. May include redness, drying and

cracking of skin. Prolonged/repeated contact may cause defatting of the skin which can

lead to dermatitis.

Inhalation May cause drowsiness or dizziness. May cause irritation to the mucous membranes and

upper respiratory tract.

Ingestion May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea,

diarrhea, and vomiting.

Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Based on the information provided, this product does not contain any carcinogens or

potential carcinogens as listed by OSHA, IARC or NTP.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 27,778.00 mg/kg ATEmix (dermal) 3,333.00 mg/kg ATEmix (inhalation-vapor) 187.96 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Hexane		2.1 - 2.98: 96 h Pimephales	1000: 24 h Daphnia magna mg/L
110-54-3		promelas mg/L LC50 flow-through	EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Hydrocarbon Propellant	2.8
68476-86-8	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Empty, depressurized containers can not be reused. Can which are pressurized or contain

liquid must be disposed of in a permitted waste management facility. Disposal should be in

accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Hexane	Toxic
110-54-3	Ignitable

14. TRANSPORT INFORMATION

Please see current shipping paper for most up to date shipping information, including Note

exemptions and special circumstances.

DOT Limited Quantity

UN/ID No UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.1

,

Revision Date: 31-May-2016

<u>IATA</u>

UN/ID No UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1

IMDG

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E	ENCS	IECSC	KECL	PICCS	AICS
			LINCS					
Hexane	Х	Х	Х	Present	Х	Present	Χ	Χ
Hydrocarbon Propellant	Х	Х	Х		Х	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane	5000 lb		RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	60-90	1.0

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane	X	X	X
110-54-3			

16. OTHER INFORMATION

Health Hazards Special Hazards NFPA **Flammability** Instability Not determined Not determined Not determined Not determined **HMIS Health Hazards Flammability Physical hazards Personal Protection**

Not determined Not determined Not determined Not determined

Issue Date: 29-Jun-2015 **Revision Date:** 31-May-2016 **Revision Note:** New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet