

# Safety Data Sheet

Issue Date: 23-Nov-2015

Revision Date: 11-Jan-2016

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Angelus No. 894 Suede Renew

### Other means of identification

**SDS #** ASP-010

**UN/ID No** UN1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** Suede Refresher

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Angelus Shoe Polish Co.  
Florence Ave.  
Santa Fe Springs, CA 90670  
Ph: 562-941-4242

### Emergency Telephone Number

**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Transparent liquid      **Physical state** Liquid      **Odor** Slightly sweet, Alcohol

### Classification

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 1
Flammable Liquids	Category 3

### Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

### Signal Word

**Danger**

### Hazard statements

Causes serious eye irritation  
Causes damage to organs  
Flammable liquid and vapor

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor/physician  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other hazards**

Toxic to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Isopropyl Alcohol	67-63-0	>15
Ethyl Alcohol	64-17-5	>20
Glycerol	56-81-5	6
Methanol	67-56-1	<1

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

**First Aid Measures**

<b>General Advice</b>	Provide this SDS to medical personnel for treatment.
<b>Eye Contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
<b>Skin Contact</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention.

<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. If not breathing, give artificial respiration. Oxygen should only be administered by qualified personnel.
<b>Ingestion</b>	IF SWALLOWED: rinse mouth. Do not induce vomiting without medical advice. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Immediately call a poison center or doctor/physician.

**Most important symptoms and effects**

<b>Symptoms</b>	Contact with eyes may cause stinging, tearing, redness, or swelling. Contact with skin may result in redness and burning. If inhaled, symptoms may include, irritation of the nose, throat, and respiratory tract. Swallowing may result in gastrointestinal irritation (Nausea, Vomiting, and Diarrhea) and central nervous system depression (Dizziness, Drowsiness, Weakness, Fatigue, Nausea, Headache, Unconsciousness), Dizziness, shortness of breath, drunken behavior, visual disturbance, fatigue, unconsciousness, complete blindness, and death.
-----------------	--

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	Treat as methyl alcohol poisoning. Treatment should include the following: Hemodialysis, the intravenous administration of ethanol (10ml per hour) to interfere with the metabolism of methyl alcohol; and the administration of sodium bicarbonate to correct acidosis.
---------------------------	--

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**Regular foam, water fog, CO<sub>2</sub>, dry chemical, Alcohol foam.**Unsuitable Extinguishing Media** Not determined.**Specific Hazards Arising from the Chemical**

Flammable liquid and vapor. Vapors may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, static discharges or other ignition sources at locations distant from product handling point. Vapors may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.

**Hazardous Combustion Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Various hydrocarbons.**Explosion Data****Sensitivity to Static Discharge** Prevent electrostatic charge build-up by using common bonding and ground techniques.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Never use welding or cutting torch on or near containers that are full or empty because product (even slight residue) can ignite explosively. Cool fire exposed containers with water spray to prevent vapor pressure build up.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet.**Environmental precautions****Environmental precautions** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

<b>Methods for Containment</b>	Persons not wearing protective equipment should leave area until cleanup is completed. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.
<b>Methods for Clean-Up</b>	Sweep up and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

**7. HANDLING AND STORAGE****Precautions for safe handling**

<b>Advice on Safe Handling</b>	Use only outdoors or in a well-ventilated area. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection.
--------------------------------	--

**Conditions for safe storage, including any incompatibilities**

<b>Storage Conditions</b>	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not store above 49°C/120°F.
<b>Packaging Materials</b>	Empty containers retain product residue and can be hazardous.
<b>Incompatible Materials</b>	Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines**

<b>Chemical Name</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Glycerol 56-81-5	-	TWA: 15 mg/m <sup>3</sup> mist, total particulate TWA: 5 mg/m <sup>3</sup> mist, respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> mist, total particulate (vacated) TWA: 5 mg/m <sup>3</sup> mist, respirable fraction	-
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. Provide sufficient ventilation to maintain exposure below TLV(s). Any use of this product at an elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Splash proof chemical safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

**Skin and Body Protection** Impervious gloves, clothes and boots. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

**Respiratory Protection** If TLV is exceeded, use a NIOSH/MSHA approved respirator for organic vapors; Refer to 29 CFR 1910.134 for respiratory protection requirements.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	Slightly sweet, Alcohol
<b>Appearance</b>	Transparent liquid	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Clear		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	No data	
Flash Point	23.88 °C / 75 °F	
Evaporation Rate	N/A	(butyl acetate = 1)
Flammability (Solid, Gas)	Not determined	
Flammability Limits in Air		
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	No data	
Vapor Density	No data	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

**Other Information**

**VOC Content** 389 g/L

**Density** 7.5 lbs/gal @ 25°C(77°F)

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization**      Hazardous polymerization does not occur.

### Conditions to Avoid

Keep away from heat, sparks and open flame.

### Incompatible Materials

Strong oxidizing agents.

### Hazardous Decomposition Products

Carbon monoxide, Carbon dioxide (CO<sub>2</sub>), Various hydrocarbons,

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

**Eye Contact**                                      Causes serious eye irritation.

**Skin Contact**                                      Avoid contact with skin and clothing.

**Inhalation**    Do not inhale.

**Ingestion**    May be harmful if swallowed.

### Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Isopropyl Alcohol 67-63-0	= 1870 mg/kg ( Rat )	= 4059 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h
Ethyl Alcohol 64-17-5	= 7060 mg/kg ( Rat )	-	= 124.7 mg/L ( Rat ) 4 h
Glycerol 56-81-5	= 12600 mg/kg ( Rat )	> 10 g/kg ( Rabbit )	> 570 mg/m <sup>3</sup> ( Rat ) 1 h
Methanol 67-56-1	= 6200 mg/kg ( Rat )	= 15800 mg/kg ( Rabbit )	= 22500 ppm ( Rat ) 8 h = 64000 ppm ( Rat ) 4 h

### Information on physical, chemical and toxicological effects

**Symptoms**    Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Carcinogenicity**

Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Isopropyl Alcohol (IPA) is an IARC Monograph Group 3 chemical. IPA is a Group 1 when manufactured by the strong-acid process.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl Alcohol 67-63-0		Group 3		X
Ethyl Alcohol 64-17-5	A3	Group 1	Known	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**STOT - single exposure**

Causes damage to organs.

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 3,748.00 mg/kg

**ATEmix (dermal)** 9,908.00 mg/kg

**ATEmix (inhalation-vapor)** 198.00 mg/L

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Isopropyl Alcohol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	1400000: 96 h Lepomis macrochirus µg/L LC50 9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static 9268 - 14221: 48 h Daphnia magna mg/L LC50
Glycerol 56-81-5		51 - 57: 96 h Oncorhynchus mykiss mL/L LC50 static	500: 24 h Daphnia magna mg/L EC50
Methanol 67-56-1		28200: 96 h Pimephales promelas mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
Isopropyl Alcohol 67-63-0	0.05
Ethyl Alcohol 64-17-5	-0.32
Glycerol 56-81-5	-1.76
Methanol 67-56-1	-0.77

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

- Disposal of Wastes**                      Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging**              Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methanol 67-56-1		Included in waste stream: F039		U154

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Isopropyl Alcohol 67-63-0	Toxic Ignitable
Ethyl Alcohol 64-17-5	Toxic Ignitable
Methanol 67-56-1	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**Note**    Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

- UN/ID No**                                      UN1263
- Proper Shipping Name**                  Paint related material
- Hazard Class**                                3
- Packing Group**                              III

**IATA**

- UN/ID No**                                      UN1263
- Proper Shipping Name**                  Paint related material
- Hazard Class**                                3
- Packing Group**                              III



**IMDG**

<b>UN/ID No</b>	UN1263
<b>Proper Shipping Name</b>	Paint related material
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Marine Pollutant</b>	This material may meet the definition of a marine pollutant

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Isopropyl Alcohol	X	X	X	Present	X	Present	X	X
Ethyl Alcohol	X	X	X	Present	X	Present	X	X
Glycerol	X	X	X	Present	X	Present	X	X
Methanol	X	X	X	Present	X	Present	X	X

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropyl Alcohol - 67-63-0	67-63-0	>15	1.0
Methanol - 67-56-1	67-56-1	<1	1.0

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen Developmental
Methanol - 67-56-1	Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Isopropyl Alcohol 67-63-0	X	X	X
Ethyl Alcohol 64-17-5	X	X	X
Glycerol 56-81-5	X	X	X
Methanol 67-56-1	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	1	0	Not determined
<b>HMIS</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical hazards</b>	<b>Personal Protection</b>
	1	1	0	Not determined

Issue Date: 23-Nov-2015  
 Revision Date: 11-Jan-2016  
 Revision Note: New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**