

28° Clipped Head Framing Nailer Kit

Product Features:

- Powerful framing nailer drives standard 28° - 30°clipped head nails
- Serrated nose tip for positive grip when toe nailing
- Protective nose tip for decking
- Special hardened driver for long, trouble free performance
- 360° directional air deflector
- Trigger for sequential and bump firing modes 1/4" air inlet
- Comes with safety glasses, oiler, hex. keys and carrying case
- It is recommended to use Stanley-Bostitch 28° wire-collated nails or Paslode 30° paper-collated (Prostrip)



MODEL	8228N
NAIL RANGE	28°-30°, 11-1/2 - 10-1/4 Ga.
NAIL SIZE RANGE	2-3/16" - 3-9/16"
NAIL DIAMETER RANGE	.113" - .131"
RECOMMENDED NAILS	Stanley - Bostitch-28° / Porter-Cable-28° / Hitachi-30°
RECOMMENDED NAILS	Paslode - 30° / Senco Frame Pro-30°
MAGAZINE CAPACITY	100
OPERATING PRESSURE	70-120 PSI
AIR CONSUMPTION	5-8 CFM (70-120 PSI)
NAILER DISCHARGE RATE	120 /min @ 90 PSI
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	19" x 4-1/4" x 14-1/2" / 9.5 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	22" x 7" x 19" / 19 lbs
UPC	7 72995 00521 5

Specifications subject to change.