



## 22" Drill Press

## **Product Features:**

- Powerful 1 HP motor
- Line interruption electro-mechanical switch needs a restart after a power failure
- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduce vibrations
- 45° tilting table for angular drilling
- Non-slip rubber feed handles
- 12 speeds
- Light socket incorporated into drill press head (standard light bulb not included)



MODEL	KC-122FC
CAPACITY	1-1/4"
CHUCK SIZE	3/4"
SWING	22"
STROKE	4-3/4"
MAX. DISTANCE FROM CHUCK TO TABLE	21-3/4"
MAX. DISTANCE FROM CHUCK TO BASE	41-7/8"
TABLE SIZE	18-3/4" x 16-1/4"
SIZE OF T-SLOT ON TABLE	5/8"
SPINDLE TAPER	MT#4
QUILL DIAMETER	75 mm
SPEEDS (RPM)	12 (180 - 4,200)
MOTOR	12.5 Amp. @ 110V, 6.25 Amp.@ 220V
VOLTAGE	110V/220V, 1 Phase, 60 Hz
PRE-WIRED AT	110V
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	18-3/4" x 33" x 69" / 320 lbs
UPC	7 72995 00256 6
	Specifications subject to chang