

# 14" x 40" Gearhead Metal Lathe

## Product Features:

- Powerful 2 HP motor
- 2 spindle bore capacity
- Safety guard with limit switch protection
- Line interruption switch system needs a restart after a power failure
- Guideway and gears in headstock are all hardened and precision ground
- Spindle foot brake incorporated in the cabinet stand for easy operation and reliable safety
- Comes complete with 7"-3 jaw chuck, 8"-4 jaw chuck, imperial and metric gears, quick change tool posts, steady rest, follow rest, 12" D1-5 camlock face plate, coolant system, full length splash guard, thread chasing dial indicator, 2 MT#3 dead centers, MT#6-MT#3 sleeve, chip tray, tool box, halogen lamp, chuck keys, hex. keys and cabinet stand (with foot brake incorporated)



<b>MODEL</b>	<b>KC-1440ML-2</b>
<b>DISTANCE BETWEEN CENTRES</b>	40"
<b>SWING OVER BED</b>	14"
<b>SPINDLE BORE</b>	2"
<b>SWING OVER CROSS SLIDE</b>	8-5/8"
<b>TAPER IN HEADSTOCK</b>	MT #6
<b>TAPER IN TAILSTOCK</b>	MT #3
<b>WIDTH OF BEDWAYS</b>	7-5/16"
<b>TOTAL TRAVEL OF CROSS SLIDE</b>	6-3/16"
<b>TOTAL TRAVEL OF TOP SLIDE</b>	3-1/2"
<b>SPINDLE SPEEDS</b>	8 (70-2,000) RPM
<b>THREAD CUTTING RANGE</b>	34 (4-56 TPI) 26 (.4-7 mm)
<b>MOTOR</b>	11 Amp.
<b>VOLTAGE</b>	240V, 1 Phase, 60 Hz
<b>ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT</b>	75" x 32" x 53" / 1,150 lbs
<b>PACKAGE DIMENSIONS (LxWxH) / WEIGHT</b>	74" x 29-3/4" x 58-1/4" / 1,375 lbs
<b>UPC</b>	7 72995 00269 6