

14" x 40" Gearhead Metal Lathe With Taper Attachment

Product Features:

- Powerful 2 HP motor
- 2" spindle bore capacity
- Safety guard with limit switch protection
- Line interruption switch system needs a restart after a power failure
- Guideway and gears in headstock are all hardened and precision ground
- Spindle foot brake incorporated in the cabinet stand for easy operation and reliable safety
- Comes complete with 7"-3 jaw chuck, 8"-4 jaw chuck, imperial and metric gears, quick change tool posts, steady rest, follow rest, 12" D1-5 camlock face plate, coolant system, full length splash guard, thread chasing dial indicator, 2 MT#3 dead centers, MT#6-MT#3 sleeve, chip tray, tool box, halogen lamp, chuck keys, hex. keys and cabinet stand (with foot brake incorporated)



MODEL	KC-1440ML-2/KM-054
DISTANCE BETWEEN CENTRES	40"
SWING OVER BED	14"
SPINDLE BORE	2"
SWING OVER CROSS SLIDE	8-5/8"
TAPER IN HEADSTOCK	MT #6
TAPER IN TAILSTOCK	MT #3
WIDTH OF BEDWAYS	7-5/16"
TOTAL TRAVEL OF CROSS SLIDE	6-3/16"
TOTAL TRAVEL OF TOP SLIDE	3-1/2"
SPINDLE SPEEDS	8 (70-2,000) RPM
THREAD CUTTING RANGE	34 (4-56 TPI) 26 (.4-7 mm)
MOTOR	11 Amp.
VOLTAGE	240V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	75" x 32" x 53" / 1,150 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	74" x 29-3/4" x 58-1/4" / 1,375 lbs
UPC	7 72995 00271 9

Specifications subject to change.