

16" Open Drum Sander

Product Features:

- All ball bearing die cast construction
- Conveyor belt tracking is easy to adjust
- Easy clamping sanding belt loading system
- 2-1/2" dust chute
- A metric and imperial depth scale is provided for thickness adjustment
- Metal stand included



Important: With its open ended design this machine can sand a 32" wide piece in 2 passes

MODEL	KC-1632DS
DRUM MOTOR	1 HP / 10 Amp.
BELT FEED MOTOR	1/8 HP
MAXIMUM WIDTH OF SANDING	2 x 16"
MAXIMUM SANDING CAPACITY PER PASS	1/64"
MAXIMUM THICKNESS OF BOARD	5"
MINIMUM THICKNESS OF BOARD	1/8"
MINIMUM LENGTH OF BOARD	2-1/4"
BELT	3" x 96"
FEEDING SPEED	0-31 SIPM
NUMBER OF SANDING DRUMS	1
SANDING DRUM SPEED	1,720 RPM
VOLTAGE	110V, 1 phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	40" x 27" x 61" / 156 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	37" x 25-1/4" x 26-3/8" / 172 lbs
UPC	7 72995 00069 2