



5.5 Peak HP 20 Gallon Air Compressor

Product Features:

- 2 cylinder cast iron single stage oil lubricated pump
- 150 PSI Max pressure for optimum tool performance
- ASME registered tank
- ASME safety valve
- Wisconsin Electric 5.5 peak HP motor with reset
- Belt drive with sturdy metal belt guard
- Large intake "Auto-drop" filters
- Air pressure regulator and easy to read pressure gauges
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- 10" pneumatic wheels and a front handle for portability



MODEL	KC-2051H2
MOTOR (PEAK)	5.5 HP
FACTORY PRESSURE SETTING (ADJUSTABLE UP TO)	95-125 PSI (150 PSI)
AIR DELIVERY @ 40 PSI	7.6 CFM
AIR DELIVERY @ 90 PSI	6.0 CFM
TANK SIZE	20 Gallon
MOTOR AMPERAGE	15/7.5 Amp.
RPM	3,450
VOLTAGE	120V/240V, 1 Phase, 60 Hz
PRE-WIRED	120V
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	39-1/2" x 20-1/2" x 31" / 145 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	35-3/4" x 19-1/2" x 31" / 155 lbs
UPC	7 72995 01094 3