



26" x 12" Dual Drum Sander

Product Features:

- 26" width by 12" thickness capacity
- Variable feed speed
- Heavy-duty base and steel frame provides stability during operation
- The parallelism between the sanding drum and the conveyor table is easily adjusted by turning adjustment screws
- Magnetic safety switch
- Twin 4" dust chutes for dust collector hook-up
- A metric and imperial depth scale is provided for thickness adjustment
- 5" aluminum sanding drum is precision balanced and driven by a V-belt



MODEL	KC-26DS
SANDING DRUM MOTOR	3 HP, 16 Amp, 220V
CONVEYOR BELT MOTOR	1/6 HP , 220V, 1 Phase
MAXIMUM WIDTH OF SANDING	26"
MAXIMUM THICKNESS OF BOARD	12"
MINIMUM THICKNESS OF BOARD	1/4"
MINIMUM LENGTH OF BOARD	5"
ABRASIVE BELT	5" x 120"
VARIABLE FEEDING SPEED	3-20 SFPM
NUMBER OF SANDING DRUMS	2
SANDING DRUM SPEED	1,550 RPM
VOLTAGE	220V, 60 Hz, 1 Phase
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	45" x 30-1/2" x 49" / 485 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	47-3/4" x 32-1/4" x 52-1/4" / 572 lbs
UPC	7 72995 00068 5

Specifications subject to change.