

Radial Drilling Machine With Safety Guard

Product Features:

- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Head swivels 180° and is easily raised and lowered
- Head travels up to 14"
- Spindle is equipped with heavy-duty tapered bearings
- Powerful 1.5 HP single phase motor
- Magnetic line interruption switch and safety guard with limit switch protection
- Complete with forward reverse switch, 1/2" chuck with key, safety guard and stand



KC-35

MODEL	KC-35
DRILLING CAPACITY	1-1/4"
MAX. DISTANCE SPINDLE NOSE TO TABLE	21-1/4"
SWING	38-1/2"
SPINDLE	MT #3
SPINDLE STROKE	5-1/4"
COLUMN DIAMETER	4-1/2"
SPEEDS (RPM)	5 (340-3,000)
TABLE DIMENSIONS	21-5/8" x 19-5/8"
HEAD TRAVEL	14"
SIZE OF T-SLOT ON TABLE	5/8"
MOTOR	8.8 Amp.
VOLTAGE	220V, 1 Phase, 60 Hz
DIMENSIONS (LxWxH)	34" x 24" x 90"
SHIPPING WEIGHT	638 lbs
UPC	7 72995 35000 1