

21" Gearhead Milling Drilling Machine With Safety Guard (600V)

Product Features:

- Magnetic line interruption switch needs a restart after a power failure
- Spindle is equipped with four heavy-duty tapered roller bearings
- Powerful three phase 1.5 HP motor
- Forward and reverse switch
- Comes complete with 1/2" chuck with key, 3-1/2" angle vise and safety guard



MODEL	KC-40HC-6
DRILLING CAPACITY	1-1/4"
MAX. DIST. SPINDLE NOSE TO TABLE	26-1/2"
MAX. DIST. SPINDLE NOSE TO BASE	47"
SWING	20-7/16"
SPINDLE TAPER	R8
SPINDLE STROKE	5"
DIAMETER OF COLUMN	4-1/2"
SPEEDS	6 (60-1,500) RPM
FACE MILL CAPACITY	4"
END MILL CAPACITY	3/4"
TABLE SIZE	23" x 7-1/2"
MAX. TABLE TRAVEL	14-1/2"
CROSS TRAVEL	6-1/4"
SIZE OF T-SLOT ON TABLE	1/2"
MOTOR	2 Amp.
VOLTAGE	600V, 3 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	38" x 37" x 78" / 630 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	29-1/4" x 33" x 73" / 690 lbs
UPC	7 72995 00405 8