

## 21" Gearhead Drilling Machine (220V)

## **Product Features:**

- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Spindle is equipped with four heavy-duty tapered roller bearings
- Powerful single phase 1.5 HP motor
- Forward and reverse switch
- Comes complete with 1/2" chuck with key, 3-1/2" angle vise and safety guard



MODEL	KC-40HS
DRILLING CAPACITY	1-1/4"
MAX. DIST. SPINDLE NOSE TO TABLE	22"
MAX. DIST. SPINDLE NOSE TO BASE	47"
SWING	20-7/16"
SPINDLE TAPER	MT #3
SPINDLE STROKE	5"
DIAMETER OF COLUMN	4-1/2"
SPEEDS	6 (60-1,500) RPM
FACE MILL CAPACITY	4"
END MILL CAPACITY	3/4"
TABLE SIZE	21-3/4" x 19-1/2"
SIZE OF T-SLOT ON TABLE	5/8"
MOTOR	8.8 Amp.
VOLTAGE	220V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	21-1/4" x 30" x 78" / 575 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	29-1/4" x 32-3/4" x 73-3/8" / 735 lbs
UPC	7 72995 15014 4
	Specifications subject to change.