

Gearhead Milling/Drilling Machine With Safety Guard

Product Features:

- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Powerful 1.5 HP single phase motor
- Spindle is equipped with four heavy-duty tapered roller bearings
- Forward and reverse switch
- Table control hand wheels have large micrometer dials graduated in .001"
- Comes complete with 3" face cutter, 3-1/2" angle vise and safety guard



MODEL	KC-45
DRILLING CAPACITY	1-1/4"
MAX. DIST. SPINDLE NOSE TO TABLE	18"
SWING	20-7/16"
SPINDLE TAPER	R8
SPINDLE STROKE	5"
SPEEDS	6 (60-1,500) RPM
FACE MILL CAPACITY	4"
END MILL CAPACITY	1-1/4"
MAX. LONGITUDINAL TRAVEL	20-1/2"
MAX. CROSS TRAVEL	8-1/4"
WORKING AREA OF THE TABLE	9-1/2" x 32-1/4"
SIZE OF T-SLOT ON TABLE	5/8"
MOTOR	11 Amp.
VOLTAGE	220V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	47" x 34" x 55" / 700 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	35-3/4" x 28-7/8" x 48-3/4" / 772 lbs
UPC	7 72995 15015 1
	Specifications subject to change