

## 28" Gearhead Drilling Machine (550V, 3 Phase)

### Product Features:

- Powerful 2 HP motor, provides ample power for production drilling
- Magnetic line interruption switch and safety guard with limit switch protection
- Quill has an internal MT #4 to accept tapered drill press accessories
- Feed selector dial and automatic power downfeed lever and tapping
- Production sized table with coolant trough and clamping slots
- Positive depth stop for quick and easy adjustment
- Built-in tool ejector
- Magnetic line interruption switch and safety guard with limit switch protection
- Comes with 5/8" (JT#33) drill chuck, chuck key, MT#4 chuck arbor, MT#4-MT#2 sleeve, MT#4-MT#3 sleeve, recirculating coolant system, work light, retractable transparent guard, drift key and tool box



<b>MODEL</b>	<b>KC-50</b>
<b>DRILLING CAPACITY IN LIGHT ALLOY STEEL</b>	1-3/8"
<b>DRILLING CAPACITY IN MILD STEEL</b>	1-1/2"
<b>CHUCK SIZE</b>	5/8"
<b>SPINDLE TAPER</b>	MT #4
<b>SWING</b>	27-1/2"
<b>STROKE</b>	7"
<b>MAX. DISTANCE SPINDLE TO TABLE</b>	26"
<b>MAX. DISTANCE SPINDLE TO BASE</b>	43"
<b>TABLE DIMENSIONS</b>	22" x 22"
<b>SIZE OF T-SLOT ON TABLE</b>	5/8"
<b>SPEEDS</b>	18 (60-870 / 120 -1,740) RPM
<b>MOTOR</b>	2.4 Amp.
<b>COOLANT PUMP MOTOR</b>	1/8 HP
<b>VOLTAGE</b>	550V, 3 Phase, 60 Hz
<b>ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT</b>	22" x 37" x 91" / 1,200 lbs
<b>PACKAGING DIMENSIONS (LxWxH) / WEIGHT</b>	83-3/4" x 24-7/8" x 44-1/4" / 1,309 lbs
<b>UPC</b>	7 72995 00478 2