

Stationary 6.5 Peak HP 60 Gallon Air Compressor

Product Features:

- Thermally protected US Motor® 6.5 peak HP motor with reset
- 2 cylinder cast iron single stage oil lubricated pump
- 150 PSI Max pressure for optimum tool performance
- 60 Gallon ASME registered tank provides longer run times
- ASME safety valve
- Belt drive with sturdy metal belt guard
- Large intake "Auto-Drop" metal filters
- Heavy-duty 1/2" ball valve and easy to read tank pressure gauge
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- High efficiency reed valves for maximum performance



| | |
|--|---------------------------|
| MODEL | KC-6160V3 |
| MOTOR (PEAK) | 6.5 HP |
| FACTORY PRESSURE SETTING (ADJUSTABLE UP TO) | 95-125 PSI (Max. 130 PSI) |
| AIR DELIVERY @ 40 PSI | 13.4 CFM |
| AIR DELIVERY @ 90 PSI | 11.2 CFM |
| TANK SIZE | 60 Gallon |
| MOTOR AMPERAGE | 15 Amp. |
| RPM | 3,450 |
| VOLTAGE | 240V, 1 Phase, 60 Hz |
| ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT | 25" x 22" x 67" / 260 lbs |
| PACKAGE DIMENSIONS (LxWxH) / WEIGHT | 31" x 24" x 73" / 270 lbs |
| UPC | 7 72995 01080 6 |