



6" x 48" Belt And 12" Disc Sander

Product Features:

- Powerful 1.5 HP, 110V/220V motor
- 2 Step activation safety switch with line voltage interruption in case of power failure
- Heavy-duty cast-iron tilting tables and body
- Belt platen is covered with a graphite pad to reduce friction and increase belt life
- Sanding belt operates vertically, horizontally or at any set angle in between
- Belt and disc safety guards
- Quick release lever for easy belt replacement
- 4" dust chute for dust collector hook-up
- Comes with aluminum miter gauge, cast-iron work stop, T-slot centre point, enclosed stand and adjustment hex. keys



MODEL	KC-790FX
BELT	6" x 48"
BELT TABLE TILT ANGLE	0 - 45°
BELT SPEED	2,250 SFPM
DISC	12"
DISC SPEED	1,750 RPM
DISC TABLE TILT ANGLE	45° ▽ - 45° △
MOTOR	1-1/2 HP, 13 / 6.5 Amp.
VOLTAGE	110V/220V, 1 Phase, 60 HZ
PRE-WIRED AT	220V
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	35" x 25" x 56-1/4" / 265 lbs
UPC	7 72995 01542 9

Specifications subject to change.