

Oscillating Spindle Sander



Product Features:

- Designed for intricate contour sanding operations
- 2 Step activation safety switch with line voltage interruption in case of power failure
- Heavy-duty cast-iron tilting table is precision ground 1" to 4" rubber drums can be fitted on both ends for full use of the entire spindle
- 4" Dust chute for dust collector hook-up
- Heavy-duty oil bath gearbox with oil level sight gauge 10 interchangeable spindles (1/4" x 5", 3/8" x 6", 1/2" x 6", 5/8" x 6", 3/4" x 9", 1" x 9", 1-1/2" x 9", 2" x 9", 3"x 9" and 4" x 9")
- Includes 3 interchangeable table inserts and adjustment keys

MODEL	KC-OVS-FX3
OSCILLATIONS PER MINUTE	75
OSCILLATIONS STROKE	1-1/2"
SPINDLE DRUM LENGTH	10 (5" to 9")
SPINDLE DRUM DIAMETER	1/4" to 4"
SPINDLE SPEEDS	1,725 RPM
TABLE SIZE	24-1/4" x 24-1/4"
MOTOR	10 Amp. @ 110V, 5 Amp. @ 220V
VOLTAGE	110/220V, 1 Phase, 60 Hz
PRE-WIRED AT	110V
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	24-1/4" x 24-1/4" x 47-1/4" / 285 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	26" x 26" x 44-1/2" / 320 lbs
UPC	7 72995 15009 0