

Oscillating Spindle Sander



Product Features:

- Rotating and oscillating effect ensures exceptional finishing results
- Precision ground heavy-duty cast-iron table
- Table can be tilted downwards up to a maximum of 45° to allow the sanding of beveled parts
- Graduated bevel scale for accurate reading of the degree of tilt
- On-board side mounted spindle and table insert storage
- A plastic 2" dust hood is supplied under the table for connection to a dust collector
- Comes standard with 3 spindles (1/4", 1/2" and 5/8") and 2 drums (1-1/2" and 2")

MODEL	KC-OVS-TL
OSCILLATIONS PER MINUTE	29
OSCILLATIONS STROKE	15/16"
SPINDLE DRUM DIAMETER	1-1/2" - 2"
SPINDLE DIAMETER	1/4" - 1/2" - 5/8"
SPINDLE SPEED	1,720 RPM
TABLE SIZE	14-3/4" x 14-3/4"
DUST HOOD OUTLET DIAMETER	2"
MOTOR	7.5 Amp.
VOLTAGE	120V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	17-1/2" x 14-3/4" x 18-7/8" / 77 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	17" x 17" x 21" / 82 lbs
UPC	7 72995 01271 8

Specifications subject to change.