

## 10" x 16" Wood Lathe

### Product Features:

- All precision-machined cast-iron bedway, headstock and tailstock construction ensures stability and minimizes vibration for smoother turning
- 10" inboard swing for bowl turning
- Maximum turning capacity of 16" between centers
- Easy access 6-speed step pulley matches speed with specific turning operation
- Large 6" toolrest for flexibility in turning positions
- Toolrest post clamp can be positioned on either side
- Complete with MT#2 live center, MT#2 spur center, 3" faceplate, steel knock-out bar, hex. keys and safety glasses



<b>MODEL</b>	<b>KWL-1016C</b>
<b>SWING OVER BED</b>	10"
<b>SWING OVER TOOLREST BASE</b>	7-1/2"
<b>DISTANCE BETWEEN CENTERS</b>	16"
<b>SPINDLE SIZE (RH THREAD)</b>	1" x 8 TPI
<b>SPINDLE SPEEDS</b>	6 (480 / 1,270 / 1,960 / 2,730 / 3,327 / 4,023 RPM)
<b>HEADSTOCK, TAILSTOCK TAPER</b>	MT #2
<b>SELF-EJECTING TAILSTOCK TRAVEL</b>	3-1/2"
<b>MOTOR</b>	1/2 HP / 1,720 RPM
<b>VOLTAGE</b>	110V, 1 Phase, 60 Hz
<b>ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT</b>	34" x 10" x 15" / 106 lbs
<b>PACKAGING DIMENSIONS (LxWxH) / WEIGHT</b>	37" x 12" x 17-1/4" / 110 lbs
<b>UPC</b>	7 72995 00332 7

Specifications subject to change.