



12" x 18" Variable Speed Wood Lathe

Product Features:

- 1 HP high performance DC motor
- Reliable single board computer microprocessor for precise control
- Precise spindle speed digital readout
- Variable speed from 450 3,800 RPM
- 24 indexing positions with spindle lock
- Work light with 18" flex. shaft for improved visibility during intricate work
- Heavy-duty precision cast iron bed ensures stability, accepts optional extension bed for turning operations up to 44"
- Comes complete with 3" faceplate, 6" and 12" tool rests with 1" post diameter, MT#2 spur centre and MT#2 heavy-duty live centre, safety goggles, knock-out rod, tool storage rack, screwdriver and 4 hex. keys



MODEL	KWL-1218VS
SWING OVER BED	12"
DISTANCE BETWEEN CENTRES	18"
SPINDLE SIZE	1" x 8 TPI
SPINDLE BORE	3/8"
SPINDLE SPEEDS	2 (450-1,800 / 950-3,800 RPM)
HEADSTOCK AND TAILSTOCK TAPER	MT # 2
GAP IN BED DISTANCE	1-1/4"
DC MOTOR	1 HP / 7 Amp.
VOLTAGE	110V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	39" x 15" x 18" / 105 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	36" x 14-1/2" x 18-3/8" / 110 lbs
UPC	7 72995 01279 4
	Specifications subject to change