

Milling Drilling Machine



Product Features:

- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Pulley cover with limit switch protection
- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in .001"
- Head swivels 360° and is easily raised and lowered
- Comes with 3" face cutter, 1/2" chuck with key, 3-1/2" angle vise and safety guard

MODEL	PDM-30
DRILLING CAPACITY	1-1/4"
MAX. DIST. SPINDLE NOSE TO TABLE	18-7/8"
SWING	16-1/2"
SPINDLE TAPER	R8
SPINDLE STROKE	5"
DIAMETER OF COLUMN	4-3/4"
SPEEDS	12 (150-2,500) RPM
FACE MILL CAPACITY	3"
END MILL CAPACITY	3/4"
MAX. LONGITUDINAL TRAVEL	17"
CROSS TRAVEL	7-1/4"
WORKING AREA OF TABLE	8-1/4" x 28-3/4"
SIZE OF T-SLOT ON TABLE	5/8"
MOTOR	11 Amp.
VOLTAGE	220V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	43" x 39" x 42" / 502 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	30-1/4" x 32" x 43-3/8" / 600 lbs
UPC	7 72995 30001 3