

2764 Aurora Avenue, Suite 100 Naperville, IL 60540 331-472-4231 Berninaofnaperville.com

Instructor: Gayle Schliemann gayle@berninaofnaperville.com



12" finished

This block uses the strip piecing technique. You will first sew the four strips together and then dissect those units into squares, which will be put into a standard 9-patch setting.

Suggested Supplies:

6" x 24" ruler

6" square ruler

14" square ruler

Seam Ripper

Nice iron

Rotary cutter 45mm or 60mm with fresh blade

Klutz glove




Figure 1.

Patchwork sewing feet. There are a variety available from BERNINA.

- #37 suitable for the 5.5mm machines
- #57 suitable for the 5.5mm machines, but with added right hand guide (like training wheels)
- #57 and #37 D for machines with dual feed
- #97 and #97 D designed for machines with 9mm stitching packaged with a screw on seam guide wall for accurate long seams

Cutting Instructions:

WOF= Width of fabric

1 strip color #1- 1 ½" x Width of Fabric ~44" (WOF)

1 strip color #2- 1 1/2" x WOF

1 strip color #3- 1 1/2" x WOF

1 strip color #4- 1 1/2" x WOF

Sewing Instructions:

- 1. Sew color #1 to Color #2 and press to color #1. (Measure to make sure that this unit is 2 ½" wide).
- 2. Sew color #3 to Color #4 and press to color #3 (Measure to make sure that this unit is 2 ½" wide).
- 3. Sew unit from step 1 to unit form step 2. Press to color #2. (Measure to make sure that this unit is 4 ½" wide).



2764 Aurora Avenue, Suite 100 Naperville, IL 60540 331-472-4231 Berninaofnaperville.com

More Cutting:

Now you will sub cut what you have sewn together into 9-4 1/2" squares.

More Sewing:

Using the picture from the top of the page, Sew the nine-patch together.

- 1. Press the seams in the first row to the left.
- 2. Press the seams in the second row to the right
- 3. Press the seams in the third row to the left.

*note- When doing patchwork it is important to press to one side for strength of the seam and butting the seams up together when joining two units.

- 4. Sew the first row to the second row. Press the seam to the first row.
- 5. Sew the unit from step 4 to the third row. Press to the second row.