

Notes

Blind Hem

| Fabricheavy material, 6" x 8" Needle |
|---|
| Stitch#2 zigzag and #9 blindstitch Needle Positionas needed |
| Blind Hem Finish one 6" edge of the fabric by oversewing with a Honeycomb stitch or Overlocker |
| Fold a 1 1/2" hem to the wrong side of the fabric and press. |
| Baste, engaging the basting ffeature on Models B 790 PLUS and B 880 PLUS otherwise elongate stitch t 6mm in length |
| Fold hem back to the right side over the basting line. |
| Sew on the extended hem allowance, keeping the folded edge next to the guide on the foot. |
| Adjust the stitch width or needle position as needed so that the needle barely stitches into the fold. |
| Mount the sample with the edges folded back as shown. |
| |
| |
| |
| |
| |
| |
| |



Notes

Hand Picked Hem

| Fabric | lightweight batiste or cotton lawn, 6" x 8" |
|-----------------|---|
| Needle | |
| Thread | 50 weight cotton thread |
| Presser Foot | BERNINA Blind Hem Foot #5 |
| Stitch | blindstitch #9 |
| Needle Position | as needed |

Handpicked Hem

Turn up a 1/2" hem along one of the 6" edges and press. Turn up the depth of the hem again and press. Fold the entire hem toward the right side of the garment, so that the garment fold is almost even with the top edge of the hem. A scant 1/16" of hem edge should be visible. This will ensure that both folds are caught by the blind hem stitch.

Place the fabric under the foot just as a traditional blind hem would be placed.

Sew the hem with Blindstitch, making sure that the zigzag catches both folds while the straight stitch falls off the edge and stitches (sewing on no fabric) forming a chain along the upper hem edge. Adjust stitch width if needed.

Press and mount the sample.



Notes

Joining Batting

| Fabric | two pieces batting, 8" x 10" |
|-----------------|---------------------------------|
| Needle | |
| Thread | Aurifil Cotton 5o wt |
| Presser Foot | BERNINA Edgestitch Foot #10/10C |
| Stitches | Rampart Stitch #13 |
| Needle Position | center |

Flat Joining Seam
Select the Rampart Stitch #_____

Cut Your batting right sides up barley overlapping in the middle. Use a rotary cutter to make a gentle curve.

Line the #10 center guide with the butted edges of batting. When the needle swings right, it takes a bite out of the right batting, When the needle swings left, it takes a bite out of the left side.



Notes

Rolled and Whipped Edge

| Fabric | lightweight cotton lawn, 6" x 4" |
|-----------------------|----------------------------------|
| Needle | |
| Thread | |
| Presser FootBERNINA m | anual Buttonhole Foot #3/3C |
| Stitch | zigzag #2 |
| Needle Position | Center |

Rolled and Whipped Edge

Clean one 6" lengthwise edge of "whiskers"

Select the Zigzag Stitch SW = 4mmmm and SL = 0.9mm Loosen the top tension to 2.25

Notes:

- The left swing of the needle should be in the fabric, while the right swing falls off of the right edge of the fabric.

- As needle swings left, it should roll fabric into a tiny rolled edge.

- The finer the fabric, the finer the needle and thread used.

Trim and mount the sample.

This edge finish is used on a single thickness of fine lightweight fabrics. It is also use as a seam finish or as an edge on ruffles, hems, etc.



Notes

Super Stretch Seam

| Fabric | Jersey knit, 4″ x 6″ |
|-----------------|--------------------------------------|
| Needle | |
| Thread | Mettler Silk Finish 50wt 100% Cotton |
| Presser Foot | BERNINA Reverse Pattern Foot #1/1C |
| Stitch | stretch |
| Needle Position | center |

Super Stretch Seam

Cut fabric in half lengthwise creating two pieces, 2" x 6" each. Select the Stretch Stitch.

Position the fabric to produce a 5/8" seam down one side. Stitch the seam; if fabric stretches, lighten the presser foot pressure (if available).

Clip one seam allowance in the middle and press one part of the seam open.

Trim and mount the sample.

Note: This stitch is good for an open seam on all knit fabrics; works well for sportswear.